ISSN (Online): 2319-7064

Impact Factor (2012): 3.358

Green Engine

V. Lohit¹, V. Nikita Verrabahu²

¹Department of Mechanical Engineering, R. M. K. Engineering College, Chennai, India

²Aeronautical Engineering, KCG College of Technology, Chennai, India

Abstract: The paper describes about the green engine, which is one of the most interesting discoveries of the new millennium. It has got some unique features when compared to other contemporary engines. This engine is one of the piston less with features like High expansion ratio, strong swirling, sequential variable compression ratio, direct intake etc. The efficiency of this engine is very high and also the exhaust emissions are near zero. The significance of the engine lies in the efficiency when the present world is facing some serious problems regarding energy crisis. Various researches on this engine is being carried out and yet to find the demerits of this engine. Generators have been produced by using green engine. Hence the GREEN ENGINE is the ENGINE OF FUTURE.

Keywords: pistonless, efficiency, exhaust, generators, future Engine.

1. Global Issues

Everyday radios, newspapers, televisions and the internet warn us of energy exhaustion, atmospheric pollution and hostile climatic conditions. After few hundred years of industrial development, we are facing these global problems while at the same time we maintain a high standard of living. The most important problem we are faced with is whether we should continue "developing" or "die".



2. Technical Features

Compared to conventional piston engines, operated on four phases, the Green engine is an actual six phase internal combustion engine with much higher expansion ratio. Thus it has six independent or separate working processes: intake, compression, mixing, combustion, power and exhaust, resulting in the high air charge rate. Satisfactory air-fuel mixing, complete burning, high combustion efficiency and full expansion. The most important characteristic is the expansion ratio being much bigger than the compression ratio. Therefore, an engine having extremely high thermal efficiency, near-zero emissions, quietness, light and small, lower cost with capability of burning of various fuels has come into being.

2.1 Direct Air Intake

Direct air intake means that there is no air inlet pipe, throttle and inlet valves on the air intake system. Air filter is directly connected to the intake port of the engine, and together with the less heating effect of air intake process, benefited from lower temperature of independent intake chamber, a highest volumetric efficiency which makes engine produce a high torque of output on all speed range is achieved. The pump loss which consumes the part of engine power is eliminated. Also fuel measuring facilities are built-in, and parts are saved.

2.2 Strong Swirling

As a tangential air duct in between combustion chamber and compression chamber, a very swirling which could lost until gas port is opened, can be formed while air is pumped into the combustion chamber. Consequently, the air-fuel mixing and the combustion process can have a satisfying working condition.

2.3 Sequential Variable Compression Ratio

This greatly revolutionary innovation can provide the most suitable compression ratio for the engine whatever operation mode it works on with burning variety of fuels. Therefore, an excellent combustion performance is attained.

2.4 Direct Fuel Injection

Direct fuel injection can provide higher output and torque, while at the same time it also enhances the response for acceleration.

2.5 Super Air-Fuel Mixing

Since the independent air-fuel mixing phase is having enough time for mixing air and fuel under strong swirling and hot situation, the engine is capable to burn any liquid or gas fuels without modifications. An ideal air-fuel mixture could delete CO emission. Also centrifugal effect coming from both strong swirling and rotation of the burner makes the air-fuel mixture denser near the spark plug.

International Journal of Science and Research (IJSR) ISSN (Online): 2319-7064 Impact Factor (2012): 3.358

2.6 Constant Volume Combustion

The fuels can generate more energy while the combustion occurs on the constant volume. Also, the constant volume combustion technology can allow the engine to have a stable combustion when the lean burning is managed. Moreover, more water can be added in to make the much higher working pressure and drop down the combustion temperature, so power is added; heat losses and NO_x emissions are decreased.

2.7 Multi-Power Pulses


The green engine operates on multi-power pulses with a small volume of working chamber contrasted to the conventional engine dose on the single power pulse with a large working chamber. Obviously, a small volume of chamber only needs little space, resulting in compact structure and limited size.

2.8 High Expansion Ratio

High expansion ratio can make the burnt gases to release much more power. In other words, the waste gases while they run out of the engine are only bringing much less energy with them. Therefore, the engine has high efficiency

3. Construction and Working

As earlier mentioned, the Green engine is a six phase, internal combustion engine with much higher expansion ratio. The term "phase" is used instead of "stroke" because stroke is actually associated to the movement of the piston. The traveling of the piston from bottom dead centre to the top dead centre or vice versa is termed a stroke. But, in this engine pistons are absent and hence, the term "phase" is used. The six phases are: intake, compression, mixing, combustion, power and exhaust. Even though the engine is of symmetric shape, the vanes traverse an unsymmetrical or uneven boundary. This shape cannot be compromised as this a result of the path taken by the intake and exhaust air. This uneven boundary is covered by the vanes in a very unique fashion.



3.1 Intake

The air arrives to the engine through the direct air intake port in the absence of an air inlet pipe, throttle and inlet valves on the air intake system. A duct is provided on the sides of the vane and rotor. The duct is so shaped that when the air moves through, strong swirls generate when it gets compressed in the chamber. The air pushes the vane blades which in turn impart a proportionate rotation in the small rotor which houses the chambers. The inlet air duct ends with a very narrow opening to the chamber.

3.2 Compression

The rushing air from the duct is pushed by the blades into the small chambers in the rotor. The volume of these chambers is comparatively very small. Naturally, the compression obtained by such a procedure is very satisfactory. As earlier mentioned, the compressed air is in a swirling state, ready to be mixed with the fuel which will be injected into the chamber when it will be place before the injector by the already rotating rotor.

3.3 Mixing

As soon as the chamber comes in front of the fuel injector, the injector sprays fuel into the compressed air. Because of the shape of the chamber, the fuel mixes well with the compressed air. The importance of ideal mixing leads to deletion of CO emission. And also because of the strong swirling, a centrifugal effect is exerted in the air-fuel mixture. Moreover, the rotation of the burner, makes this centrifugal effect all the more effective. Mixing phase has enough time to produce an ideal air-fuel mixture as the spark plug is positioned towards the other end of the rotor or burner.

3.4 Combustion

As the chamber rotates towards the "end" of its path, it is positioned before the spark plug. A spark flies from the plug into the air-fuel mixture. Because of the mixing phase, the air-fuel mixture is denser near the spark plug, thereby, enabling lean-burning of the charge and also a uniform flame front. As soon as the whole charge is ignited, the burner rotates to position itself in front of the narrow exit.

3.5 Power

The expanded gas rushes out of the chamber through the narrow opening, thereby pushing the name in the process. The sudden increase in volume ensures that more power is released. Or in other words, the thermal energy is fully utilized.

3.6 Exhaust

As the thermal energy is fully utilized, the exhaust gases bring along comparatively less heat energy. This mainly helps in the thermal efficiency of the engine. It raises the engine's thermal efficiency and also because of the complete burning of the charge, poisonous gases like CO are absent in the exhaust emissions.

Volume 3 Issue 11, November 2014 <u>www.ijsr.net</u> Licensed Under Creative Commons Attribution CC BY

4. Advantages

As obvious from the technical features which include effective innovations, the advantages of the Green engine over the contemporary piston engines are many.

4.1 Small Size and Light Weight

As Green engine is very compact with multi-power pulses, the size and weight could be 1/5 to 1/10 of the conventional piston engines on same output. Its power to weight ratio could be more than 2 hp per pound without supercharge or turbo charge.

4.2 Limited Parts

There are only some dozens of parts easy to be manufactured in the engine structure.

4.3 High Efficiency

Because many great innovations are being employed in the engine design such as: direct air intake, sequential variable compression ratio, super mixing process, constant volume combustion, controllable combustion time, high working temperature of the burner, high expansion ratio and self adapting sealing system etc., the thermal efficiency of the engine could be potentially as high as 65 %, even more if water add-in technology is to be considered.

4.4 Multi-fuels

Due to six phases of working principle, super air fuel mixing process and constant volume combustion with controllable time, the Green engine becomes the only real multi-fuel engine on our planet; any liquid or gas fuels can be burnt well. Also it would be ideal to coal powder if special antiwearing material is employed.

4.5 Smooth Operation

Due to inherence of good dynamic and static balance the performance of the Green engine is as smooth as an electric motor.

4.6 Quietness and Low Exhaust Temperature

Burst out under small amount of mixtures, free of vibrations, and high expansion ratio make the Green engine much quieter. It is really environment-friendly. Green engine vehicles could transport troops on the battlefield of the future, and could serve as a vital source of auxiliary power in combat. This is because these engines are quiet, flexible and operate at low temperature, making them ideal for use in "stealth" vehicle.

4.7 Low Cost

Limited parts, small in size, light in weight and depending upon current mature materials and manufacturing technologies, mean that it would be done at much lower cost on manufacture, transportation, installing to other devices, and maintenance

5. Conclusion

The Green engine's prototypes have been recently developed, and also because of the unique design, limitations have not been determined to any extent. But even in the face of limitations if any, the Green engine is sure to serve the purpose to a large extent.

References

- [1] Sibley, Brian (1995). *The Thomas the Tank Engine Man.* London: Heinemann. ISBN 0-434-96909-5.
- [2] ^ "The Real Stories Database book 23, story 2". (*Real life events that inspired the Rev W Awdry*). The Real Lives of Thomas the Tank Engine. Retrieved 22 October 2010.
- [3] **Green Engine** Low RPM High Torque Pressure Driven Turbine for Top Efficiency Power Modulation. Peers reviewed paper - Published in The Proceeding of Turbo Expo 2007 of the IGTI.

Author Profile



V. Lohit (R. M. K. Engineering College, Anna University, Chennai, Tamilnadu, India



V. Nikita (KCG College of Technology, Chennai, Tamilnadu, India