# A Survey on Adaptive Content Based Image **Retrieval System Using Neural Network**

#### Pratima R. Jadhav<sup>1</sup>, Rashmi S. Phalnikar<sup>2</sup>

<sup>1</sup>Pune University, MIT College of Engineering, Kothrud, Pune 411038, Maharashtra, India

<sup>2</sup>Professor, Pune University, MIT College of Engineering, Kothrud, Pune 411038, Maharashtra, India

Abstract: In several aspects of medical, technology, aerospace, bio-informatics, government organization, large collections of digital photographs are being created. A number of these collections are formed due to the product of digitizing existing collections of analogue images, diagrams, sketches, paintings, and documents. Generally, the only method of exploring these collections was by browsing or indexing of keywords, Digital photograph databases nevertheless, start the way to content-based searching. In this paper, we have present a method that has no previous knowledge about the image within the database, but retrieval is done considering the content information of the images likely to be called as content based image retrieval. Here we are trying to improve the image retrieval system for more accuracy and efficiency by using Radial basis Function neural network. This deals with multilayer feed forward network perception. By using this methodology we can easily find out exact relevant image according to the query provided by the user. The Scale Invariant Feature Transform (SIFT) is one of the most local feature detector and descriptors which is used in most of the vision software. In this paper regarding CBIR system we can utilize SIFT algorithm to extract the local features of the images. Also Backpropagation methodology, which is a managerial system for learning is utilized for training the neural network. We can use backpropagation for computation of errors in backward direction. Also k means clustering is applied to clustering Parameterize Gaussian function application. At the end actual and observed outputs are compared to calculating actual correct output.

Keywords: content based image retrieval, Radial basis Function, SIFT, and k means clustering.

#### 1. Introduction

In this paper we survey some technical facets of recent content-based image retrieval systems. Methods which are based on neural networks also have now been produced for content based image retrieval. We are applying neural network in CBIR because of their flexible learning capability. Unsupervised clustering is offered by neural networks in addition to monitored learning systems for the access of images. Recent inspection in image retrieval implies that substantial development in retrieval performance needs methods that, in a certain sense, "understand" the content of the image and queries. Lately, image retrieval analysts have used the application domain information to find out appropriate associations between queries and images.

The efficient and notable functions of the multilayer understanding [1] with content based image retrieval system allows us in opinion on the prior information, for classification of the numerous conditions solution to those particular images. The concept behind would be to categorize the image varies with the exceptional function of Radial basis function through the image processing of retrieving. The multilayer understanding provides people a new way of orientation in the precision of prediction through the content based image retrieval [2]. In the procedure of locating images, changing of the text based retrieval to the content based retrieval [3] is quite significantly a tough and challenging job subsequent with a multilayer perception of the reliability in prediction of the provided input image.

Method of Image searching is one of the finest solutions that must be supported by such systems. Basically there are two basic techniques have already been placed to allow exploring on image collections: one centered on image content information and the other is centered on image textual metadata. The initial retrieval strategy is dependent on appending textual metadata to each image and employs conventional repository query methods to access them by keywords [4].

Generally, two different techniques have been used to permit searching on image collections: one depends on image textual metadata while another based on information contents in an image. The first retrieval strategy is based on attaching textual metadata to every image and uses the traditional database query method to retrieve them by keywords but, these techniques need a prior annotation of the repository images, which is really a very time-consuming and laborious task. Moreover, the annotated method is generally inefficient since the people, not making the annotation in a systematic way. Actually, various people tend to make use of various phrases to explain a same image characteristic. The lack of systematization in the annotation method reduces the efficiency of the keyword-based image search. Image retrieval techniques perhaps not held speed with the collections they're searching. The disadvantages of these techniques are due both to the image representations they choose and with their ways of accessing those representations to locate images. The issues of image retrieval are getting widely known and the search for solution is significantly active region for development and research.

Decades of study has been undergone with textual images of exploring and introducing the explanation for that particular image, but here the significant disturbance occurred in description orientation which depends upon individual means of promoting the concept concerning about the image[5]. To overcome this ambiguity of image description textually we are moving towards a technique termed "Content-Based

# Volume 3 Issue 11, November 2014 www.ijsr.net

Image Retrieval (CBIR) systems". In these techniques, image processing algorithms (usually automatically) are used to acquire function vectors that represent image properties such as for example shade, structure, and color[6],[7].

In CBIR system, it's probable to retrieve images related to one chosen by an individual (query-by example). Thereby we are able to overcome the drawbacks of the text centered retrieval systems .The principal benefits of this method is the possibility of an automatic retrieval method, diverse to the time and effort needed to annotate images. In this report it was focused on image classification of numerous atmospheric situations on our planet map/remote sensed image. Usually Classification can be carried out with the support of numerous filtration practices but to be able to categorize the image a sophisticated system named Neural Networks is used.

### 2. Literature Review

This paper [8] deals with automatic system to discover and classifies the kind of hematomas applying synthetic neural network algorithm for CT photographs of various patients. The technique composed of four stages, first preprocessing conducted on the brain CT photographs, next histogram based centroids initialization for K-means clustering algorithm to segment the photographs in various clusters centered on the strength values of pixels. Third stage contains feature extraction from segmented image. On the last stage, artificial neural network has been developed and trained based on the characteristics extracted from the photographs. Trained artificial neural network (ANN) classifies the kinds of hematoma relating to their features.

Veera Jyothi et al.[9], stated that, in the initial strategy the retrieval strategy must be flexible such that it can provide the preferences of various users. Relevance feedback (RF) understanding has been proposed as a strategy directed at reducing the semantic gap. An essential remark when developing a customized CBIR system is that, eventually, the semantic model of an image is defined by individuals and therefore individuals are a fundamental part of such systems. This is strengthened by the fact that, in comparison to early literature which highlights the search for a "single best feature," more recent study is dedicated to "individual in the loop" approaches [10]. Thus, when seeking to reduce the semantic difference and therefore meet with the efficiency issues experienced in practical CBIR applications, RF understanding remains an extremely encouraging research direction.

The other technique [9], predicated on RBF neural networks, is dependent on deteriorating visual items into sub-objects. Low-level features of sub- items (like texture, color and size) and the common relations between them are employed for the elicitation of individuals' queries. Target programs are mainly involved multimedia and atlases encyclopedias which let an individual to look for an item predicated on a memorized image.

In this paper [11], the key purpose of the image mining is to eliminate the information reduction and extracting the significant data to the individual expected requirements. The photographs are preprocessed with different methods and the texture computation is extremely focused. Here, photos are clustered predicated on RGB Components, Texture values and Unclear C mean algorithm. Entropy can be used to examine the photos with some tolerance constraints. This program can be utilized in future to categorize the medical photographs to be able to detect the proper illness approved earlier.

Additionally, few authors have proposed a method that is based on combination of structure and shade characteristics. In this paper [12], one or two dimensional histograms of the CIE Laboratory chromaticity coordinates are utilized as color features. Structure characteristics applied here are extracted applying distinct wavelet frame analysis. Chun *et al.* [12] proposed a CBIR technique predicated on an effective combination of multi resolution structure and shade features. The shade characteristics utilized in this paper are color autocorrelation programs of the saturation and hue aspect pictures in HSV shade space are used. The structural characteristics used contain block huge difference of inverse probabilities and block deviation of local relationship coefficient moments of the value aspect image.

A survey of CBIR techniques based on relevance feedback strategy produces [13]. This report considers the high-level concepts within an image. This paper [14] presents an interactive genetic algorithm to incorporate human computer conversation and attempts to utilize user's subjectivity in a retrieval process using an individual defined fitness function. Contrasts are created between two structure recognition using neural and statistical methods.

Eventually, neural network based strategy for image processing is defined in [15], which reviews more than 250 Programs of neural networks in image processing and examine the probable and the current future role of neural networks, particularly feed-forward neural networks.

This paper [16] first combines grid and segmentation module, feature extraction module, neighborhood and Kmeans clustering module to build the CBIR system. Moreover, the idea of locality section which identifies the side of each grids of the picture is first added in this paper. This system architecture uses the idea of the fragment based code book into the CBIR system. The result of experiment confirms that the proposed CBIR system architecture attempts a better solution for image retrieval. This sculpt signify the first time in which merge new module and method projected in the paper have been incorporated with CBIR system.

This paper [17] allows one of the efficient retrieval strategies in CBIR, where the usage of IGA allows effective and accurate effects in comparison to the conventional methods that are derived from visible features; the IGA strategy has an active system to link the difference between visible features & individual perception. Along with data of a graphic & entropy additionally with texture descriptor applying GLCM allows important aid in characterizing the image. As these features & activities of the IGA method of image retrieval comes up a job of CBIR at a more substantial level.

#### International Journal of Science and Research (IJSR) ISSN (Online): 2319-7064 Impact Factor (2012): 3.358

This paper [18] provides a comprehensive review of new function towards narrowing down the 'semantic distance '. We've identified five major types of state-of-the-art techniques: (1) using an object ontology to determine high-level Focusing on the differences between CBIR with high-level semantics and traditional techniques with low-level functions, this paper also provides of good usable ideas into how to acquire salient low-level functions to aid 'semantic distance' reduction. In addition, recent techniques in the picture likeness calculation are explained.

In this paper [19], global picture property based CBIR utilizing a feed-forward back propagation neural network is proposed. At the outset, the neural system is prepared about the peculiarities of pictures in the database. The picture peculiarities considered here are color histogram as shade descriptor, GLCM as composition evaluator where as edge histogram as edge evaluator. The preparation is done using back proliferation calculation. This prepared when introduced with a query picture recovers and shows the pictures which are pertinent and similar to a query from the database. The results demonstrate a significant change regarding the accuracy and review of picture recovery. A normal recovery exactness of around 88% and a normal review rate of around 78% is accomplished utilizing the proposed approach over SIMPLI city venture database

The SIFT (Scale Invariant Feature Transform) key points defined in this report [20] are especially useful for their distinctiveness, which allows the correct fit for a key point to be selected from a big repository of other key points. Any key points may be extracted from common pictures, this leads to robustness in removing little items among the clutter. The fact key points are noticed around a complete range of machines means that little regional characteristics can be found for matching little and much occluded items, while big key points perform well for pictures at the mercy of noise and blur. This report presents the key points recognition by utilizing the Radial Schedule Function.

#### 3. Analysis of previous work

Name of Author	Paper	Description	Limitations
[8] Bhavna	Classification of Hematomas in	This paper deals with an automated system to	Classification need to be enhance using
Shanna, Prof. K.	Brain CT Images using Neural	detect and classify the type of hematomas	different types of training algorithm.
Venugopalan	Network	using an artificial neural network algorithm	Also need to develop a technique for
		for CT images of different patients.	finding the location and the exact size
	Communities Studie of Normal	Descent the existing mothed and image	of hematomas.
[9] MS.B Veera	Notworks for Image Patricual	retrievel with relevance feedback and new	It is required to investigate the
Fswaran	Networks for finage Kettlevar	algorithm which is based on an approximation	learning into the PRRL framework in
Lowaran		of user preferences by a neural network	future
		of user preferences by a neural network.	Tuture.
[16] Jan-Ming Ho	A Novel Content Based Image	Stated novel system design for CBIR system	Required to construct a generalized
Shu-Yu Lin, Chi-	Retrieval System using K-means	which merges methods including color	query technique which amplifies the
Wen Fann, Yu-	with Feature Extraction	analysis and content-based image, as well as	system searching capability and offer
Chun Wang, Ray-		methods for data mining. Idea of	more correct content descriptions of
I Chang		neighborhood color analysis section which	places of interest by performing color
		also identifies the side of every grids of the	feature examination and CCH image
51014 1		picture is first added in this paper	extraction concurrently
[19]Arvind	Content-Based Image Retrieval	A global picture properties based CBIR uses	Accomplishing the CBIR system
Nagathan, Mrs I.	System Using Feed-Forward	a feed-forward back propagation neural	bearing in mind more low-level picture
Manimozin	Network	trained about the features of images in the	knowledge neural network, which may
	Network	database	establish to be very quick and precise
		database.	one
[20] Shraddha	Radial Basis Function used in	An approach is stated for an well-organized	The key features which are produce are
Kumar, Shweta	CBIR for SIFT Features	CBIR system utilizing Radial basis function	huge in numbers so this matching
Singhal, Ankita		(RBF) which can experience into best results	procedure may take a huge time to
Sharma		than other existing CBIR. The stated	recover the image from the database
		approach employ SIFT to extract the	
		properties from the database.	

### 4. Conclusion

The new measures of content based image retrieval by using RBF neural network techniques for retrieving the images, were clustered into predefined clusters for instant image retrieval and let a great searching for the most applicable images from large databases. RBFNN is a method which uses Differential Evaluation and Gaussian features to retrieve images that are identical to initial image given to the images in the database. This work can enhance with Fuzzy C-means clustering technique.

### References

- RFu Zhen Zhu, Jin Zong Li, Bing Zhu, Dong Dong Li,Research on Image Super-Resolution Reconstruction Based On BPNN and RBFNN, Applied Mechanics and Materials (Volumes 20 – 23),Pages 445-45, published on : January, 2010.
- [2] Harri Niska, Minna Ratnama, "Evaluation of an integrated modeling system containing a multi-layer perception model and the numerical weather prediction model HIRLAM for the forecasting of urban airborne

# Volume 3 Issue 11, November 2014

<u>www.ijsr.net</u>

Licensed Under Creative Commons Attribution CC BY

pollutant concentrations", Atmospheric Environment Volume 39, Issue 35, conference on : November 2005, Pages 6524-6536.

- [3] Feature selection using localized generalization error for supervised classification problems using RBFNN. Volume 41, Issue 12, published on: December 2008, Pages 3706-3719.
- [4] S-K Chang, T. Kunii "Pictorial database Applications", IEEE Computer 14 published on : 1981 (11)(1981) 13-21.
- [5] P. G. B. Enser, Pictorial information retrieval, Journal of Documentation 51 (2) published on : 1995, pp 126-170.
- [6] H. Lieberman, E. Rosenzweig, and P. Singh. Aria: An Agent for Annotating and Retrieving Images. IEEE Computer, 34(7):57–62, published on : 2001.
- [7] M. Flickner, H. Sawhney, W. Niblack, Q. Huang J. Ashley, B. Dom, M. Gorkani, J. Hafner, D. Lee, D. Petkovic, D. Steele, and P.Yanker. Query by Image and Video Content: the QBIC System. IEEE Computer, 28(9):23–32, published on : Sep 1995.
- [8] Bhavna Shanna, Prof. K. Venugopalan," Classification of Hematomas in Brain CT Images using Neural Network", Issues and Challenges in Intelligent Computing Techniques (ICICT), 2014 International Conference on 7-8 Feb. 2014
- [9] Ms.B Veera Jyothi, Dr. Kumar Eswaran," Comparative Study of Neural Networks for Image Retrieval, published on: 2010 International Conference on Intelligent Systems Modeling and Simulation"
- [10] Doulamis, N., & Doulamis, A. (2006). "Evaluation of relevance feedback schemes in content-based in retrieval systems" Signal Processing: Image communication, Vol 21, Issued on 4 April 2006, 334-357
- [11] A.Kannan, Dr.V.Mohan, Dr.N. Anbazhagan ," Image Clustering and Retrieval using Image Mining Techniques", IEEE International Conference on Computational Intelligence and Computing Research, Publication year : 2010
- [12] Y. D. Chun, N. C. Kim, and I. H. Jang, "Content-based image retrieval using multi resolution color and texture features," IEEE Trans. Multimedia, vol. 10, no. 6, publishedon:Oct.2008.
- [13] Chih-Chin Lai, and Ying-Chuan Chen, "A User-Oriented Image Retrieval System Based on Interactive Genetic Algorithm," IEEE TRANS. Instrumentation and measurement, VOL. 60, NO. 10, pp. 3318 – 3325, Conference on : OCTOBER 2011.
- [14] Tasweer Ahmad, Ahlam Jameel, Dr. Balal Ahmad, "Pattern recognition using statistical and neural techniques," IEEE CONFERENCE. Computer Networks and Information Technology, pp. 87 - 91, 11-13, published on: July 2011.
- [15] M. Egmont-Petersen, D. De Ridder, and H. Handels, "Image processing with neural networks - a review," Pattern Recognition, 35:2279-2301, accepted on 21 August 2001.
- [16] Jan-Ming Ho, Shu-Yu Lin, Chi-Wen Fann, Yu-Chun Wang, "A Novel Content Based Image Retrieval System using K-means with Feature Extraction ",issue date: 2012, International Conference on Systems and Informatics (ICSAI 2012)
- [17] Shrikant Chavate, Prof. Parul Dihulia Prof. Vikas Gupta, "An approach used for user Oriented Content Based

Image Retrieval using Interactive Genetic Algorithm", International Journal of Advanced Research in Computer Science and Software Engineering, Volume 3, Issued on 11, November 2013

- [18] K. Vijay Kumar, Dr.R.Rajeswara Rao, V.Subba Ramaiah Jhansi Rani kaka,"Content Based Image Retrieval SystemConsume Semantic Gap", International Journal of Computer Science andInformation Technologies, Vol. 3 (5), issued on : 2012,5231-5235
- [19] Arvind Nagathan, Mrs I. Manimozhi "Feed-Forward Backpropagation Neural Network ", International Journal of Computer Science Engineering (IJCSE), Vol. 2 published on 04 July 2013
- [20] Shraddha Kumar, Shweta Singhal Ankita Sharma, "Radial Basis Function used in CBIR for SIFT Features", International Journal of Advanced Research in Computer Science and Software Engineering, Volume 2, Issued on : 4, April 2012

## **Authors Profile**

**Pratima Jadhav** completed her Bachelor of Engineering in 2013 from Sinhgad College of engineering, Pune. Presently she is doing her master's from Maharashtra Institute of Technology College of engineering, Pune. Her research interests are artificial neural networking, image processing and data mining.

**Rashmi Phalnikar** completed her Bachelor of Engineering in 1991 from Bharathi Vidyapeeth College of engineering, Pune. Presently she is pursuing her Ph.D. from NIT, Surat and is Asst. Professor in Maharashtra Institute of Technology College of engineering, Pune. Her research interests are data mining and software engineering.