

# Link-Stability and Time Consumption Scheme for Mobile Ad-hoc Wireless Networks

Shaik Jareena<sup>1</sup>, P. Anjaiah<sup>2</sup>

<sup>1</sup>M. Tech student, Department of CSE, Anurag Group of Institutions, Hyderabad, India

<sup>2</sup>Assistant Professor, Department of CSE, Anurag Group of Institutions, Hyderabad, India

**Abstract:** Energy efficient routing is be one of the most essential design measure for MANET because mobile nodes are battery powered with bounded capacity and which cannot be recharged when ever needed. So, MANET routing is challenged by power and bandwidth constraints. When mobile nodes run out of power, the network obtains partitioned and thus a few sessions are disconnected. In order to solve this problem and to attain efficient energy consumption, several solutions have been proposed. All those works are finished as the extension of the already existing adhoc routing protocols such as Proactive, Reactive and Hybrid Routing. Since table-driven protocols consume additional energy compared to on-demand protocols, the proposals made modifications to existing reactive protocols. The majority of the energy-aware protocols referenced here are implemented as modifications of the basic routing protocols using energy-sensitive metrics. Link stability is also a significant challenge of MANET routing. Several routing algorithms have been proposed for provided that QoS in terms of link stability. In this work we focused on evaluating how these approaches and algorithms influence the energy consumption in the mobile devices and how stable routes are founded in the network.

**Keywords:** Energy consumption, Energy-aware, Energy efficient routing, MANET, Routing Protocol.

## 1. Introduction

A Mobile Ad-hoc Network (MANET) is a self organizing network collected of mobile nodes connected by wireless links without any fixed infrastructure. These types of networks reveal the features such as dynamic topologies, bandwidth constrained operation, vulnerable to attacks, variable capacity links and energy constrained operation. The characteristics of MANET such as de-centralized operation, rapid deployment, dynamic multi-hop etc makes it suitable for the application like emergency rescue operations, military battle fields, smart offices, etc. However, broad deployment of MANET has not come yet due to the challenges of MANET [7] such as security, routing and reliability, QoS, power consumption etc among which energy issue is a fundamental one. Energy efficient schemes can impact on the battery power and extends the lifetime of the network while wireless communications use large amount of energy. In wireless scenario, it is a distributed environment, and several energy is consumed for neighborhood transmissions: such as nodes spend their batteries not only by sending their own packets, but also by just overhearing packets from additional nodes. Energy is also spent by forwarding packets for others. So, power efficient routing is also a most significant design challenge for MANET routing. For mobile nodes, power failure can difficulty affects its routing responsibility [8] and there by affects the network performance. So, the energy of nodes should be utilized optimally such that, they can perform their functionality successfully. There are energy management techniques that focus on minimizing energy consumption within the network. It is based on making decisions about when to activate or shut down the system components.

As MANET is a multi hop network, the packets are to be sent from source node to destination throughout a number of intermediate nodes. So, the successful delivery of packets

depends on the battery resource of each and every nodes and it must be used efficiently in such a manner that will not lead to the early termination of network. Thus, the main objective of all energy efficient routing protocols is to find an active route with better power status among a number of routes between source and destination. When considering the networks nodes for routing, a path between a source and destination is said to be stable if it consists of most stable neighbors at each hops between them. Features of ad hoc networks such as node mobility, channel fading, interference and absence of infrastructure etc results in frequent link breakages. It also makes the links not very much error resilient. For any routing protocol, it must choose a stable path.

MANET routing protocols are including the responsibility to discover and maintain routes between nodes in a dynamic topology by using least resources. They are classified into three main groups such as Reactive routing protocols, Proactive routing protocols and Hybrid routing protocols [9]. Routing is important in MANET due to the following Reasons,

- a) Host mobility: It is due to the dynamic topology that alters over time. The routing protocol should be capable of managing link failure/repair due to mobility.
- b) Distributed Environment: Minimum control overhead as there is no any centralized control.
- c) Bandwidth constrained: Total bandwidth is distributed
- d) Energy constrained: Battery resource be constrained

Following are the major characteristics of MANET routing

- Distributed Operation
- Efficient ie; low control overhead
- Self-configuration
- Resilience to changing network topology

An efficient routing protocol must maximize network throughput and lifetime, whereas minimizing delay in transmission. Routing protocols coming under energy awareness be required to balance battery lifetime, Delay constraints and routing efficiency in order to attain a better route discovery. The ordinary means of energy consumption in routing happens throughout exchange of route information. In case of route with small quantity of hops, energy is consumed importantly compared to a route with large number of hops. The lifetime of a node is humiliated as it is used more frequently.

In this work, we concentrate on analyzing performance of various energy-aware and link stability based routing protocols. The focus is given to the power consumption and link stability aspects of each protocol. The Link Stability and Energy Aware Routing Protocol in Distributed Wireless networks [1] accounts for link stability and least drain rate energy consumption by using a original strategy. It utilizes a bi objective optimization formulation for the correctness of proposed solution. Energy Efficient, Secure and Stable routing protocol for MANET [2] is another protocol which combines the aspects of both energy efficiency and stability along with safe routing. This protocol is incorporated with AODV and refined version of Stable and Secure Routing protocol (SSRP). EE-OLSR [3] is one more approach towards energy efficient routing. It is a highly developed version of classical OLSR protocol including some modifications in MRP selection. Link Stability Routing protocol under video transmission for MANET [4] proposes a modified version of existing AODV protocol to discover stable path for sending video and data packets. It is proficient to cope up with the node mobility. Energy Efficient Routing Protocol Avoiding Route Breaks based on DSR [5] is proposed to decrease the cost of managing the link failures by evading route breaks. It considers both link and node stability as a metric. QoS based Power Aware Routing in MANETs [6] selects an energy stable end-to-end path. The bandwidth and energy constraints are built in into DSR route discovery mechanism. It also provides a route repair mechanism in case of link failures.

Rest of the paper is organized as follows. Section II gives a performance evaluation of selected energy efficient routing protocols; section III provides the evaluation of link stability based routing protocols and their performance; Section IV summarizes the concert evaluation and conclusion of this work.

## 2. Performance Evaluation of Energy Aware Routing Protocols

As energy is a vital criterion for routing, the majority of the research works are going under this section. All the works are done as a modification of existing ones but having disadvantages also. This is because no any approach can achieve better in every network conditions. In wireless networks, as the nodes functions are solely based upon their battery level, the energy consumption should be effectively managed. Only by believing the energy consumption of the network, we cannot predict the energy efficiency of the system. For that, both the network lifetime and node lifetime

should be considered. So that, energy aware routing protocol [10] has to be designed in such a way that, it prolongs the network lifetime along with high performance. In Minimum energy routing, route with minimum energy consumption can get frequently used and its energy obtains exhausted leading to failure of nodes. Energy efficiency can be attained by considering different parameters in routing like energy of nodes, battery level etc. The regular alternatives for maintaining efficient energy in a network are;

- a) Minimize the energy consumption used for packet transmission and reception
- b) Exploit time taken for network partitioning suitable to link breaks
- c) Minimize the variations in node's energy level
- d) Total cost for sending a packet should be minimized.

There are two approaches for energy efficient routing. First is called transmission power control approach in which it decreases the total energy consumed per packet transmissions. As discussed earlier, it will lead to network failure since similar paths are being used repeatedly. Another approach is to extend the system lifetime which completely focuses on load balancing of nodes. There are a few fundamental concepts used for efficient energy consumption. They are,

- a) **Residual Energy**-It provides battery status indicating the remaining battery capacity of a node.
- b) **Energy Drain Rate**- It gives the rate at which a node spends its energy. This metric must be used to estimate node lifetime. For an proficient routing, energy drain rate cost must be minimized.

Floriano De Rango et al. proposed a Link Stability and Energy Aware Routing protocol (LEAR) protocol [1], in which the next hop towards destination is the neighbor node that maximize (minimize) the joint link-stability-energy metric. The energy needed to send a packet is calculated while ignoring the energy spent for overhearing a packet. Power dissipation is calculated in terms of both power consumption at transmitter and receiver. For any node  $i$ , its non destination neighboring node  $j$  is selected as a node that has enough energy to receive the information sent from node  $i$  and which is also accomplished of transmitting the information to one more relay node. For any node, the energy to transmit the packet should be lower or equal to the residual energy. least amount of drain rate along with drain rate index and residual energy is considered for measuring the energy dissipation rate of a given node.

In Energy Efficient, Sunil Taneja and Ashwani Kush proposed Secure and steady Routing Protocol for MANET [2], a routing mechanism that affords energy efficient, secure and stable routes. Here, the Secure Routing done in three steps. Diffie-Hellman Algorithm is utilized for generation of secret key and hashing to produce subsequent keys over selected route. Here, Encryption and Decryption is performed using XOR operation. The Energy Efficient and Stable Routing is achieved by means of a per hop power aware forwarding which is based on some threshold energy value  $E_{Th}$ . Even though this protocol gives a Stable and

Energy efficient algorithm with best packet delivery ratio which is easy and robust, it must not support large traffic and enhanced TCP connections. QoS is also not ensured and there is no multicast transmission support.

Floriano De Rango and Marco Fotino in their work EE-OLSR [3]: Energy Efficient OLSR Routing Protocol for Mobile Ad-Hoc Networks introduced a routing protocol to prolong network lifetime without losses of performance. It uses the concept of Multi Point Relays (MPRs), which diminishes the message overhead. In the EA-Willingness Setting mechanism, each node related with variable used "willingness" where, longer the node lifetime- HIGH Willingness and vice versa. Overhearing Exclusion is one more feature where OLSR does not obtains any advantage from unicast network information. It utilizes Energy-aware Packet Forwarding for route discovery. EE-OLSR outperforms OLSR by providing an improved traffic load balancing and throughput. It affords a normalized control overhead, high packet, enhanced node life time, delivery ratio, and lower end-to-end delay.

In the work by Vinay Rishiwal et al. , QoS Based Power Aware routing in MANETs [6], the proposed mechanism chooses an energy stable, QoS constrained end to end path. It makes the routing in two phases, where first phase deals among Route discovery with bandwidth and energy constraints and the second phase deals among Route repair mechanism for finding a new energy stable path. Route discovery algorithm achieves an Energy based path selection. The work also affords a mechanism for Route maintenance by considering the cases such as link failure due to energy depletion and Topological changes. This protocol give ups better throughput, better packet delivery ratio, average end to end delay and efficient route reconstruction. But a priori estimation of bandwidth and admission control is wanted to ensure bandwidth availability which is its drawback.

### 3. Performance Evaluation of Link Stability Based Routing Protocols

In Link stability and Energy Aware Routing Protocol [1], the node among best trade-off between the energy consumption and link stability be chosen. The mechanism uses a statistical based approach to differentiate the most stable link from others. For that, the link residual life time is calculated which gives a measure of the link stability. Classification of the links would be done on the basis of link ages according to a coefficient  $R_{i,j}(a_{i,j})$ . But one disadvantage of this concept is that, it will not encourage the discrimination of links with same age. So, the travelled distance is also is taken into consideration where, the crossed distance is stored and its average is taken. This is selected why, if there exists two or more links with similar residual energy. In this case, link among shorter average distance is selected. This mechanism will not consider the number of reordering operations of the links with different residual lifetimes. It concludes that, higher the residual lifetime for a link, the reliability will be higher. If the average travelled distance be higher, chances for link breaks is also higher.

Sachidanandh S Joshi proposed Link Stability Routing Protocol Under Video Transmission [4] for MANET, a routing protocol for video applications with higher bandwidth and reliability requirements. Here, Route discovery is based on stability of the path. Neighbor nodes with maximum hello packets are considered as more stable. It is found out using Neighbor Stability i.e., Consistency of neighbors and Path Stability i.e., Path consistency between source and destination. The stability metrics utilized are hello count and link loss. These Metrics are appended on request packets to get measure of stability of paths. The mechanism ensures high video delivery ratio and high throughput. But, all of the functioning is based on assumption that all nodes will participate and also it concentrates only on path stability.

Ashish Kumar et al. addressed an Energy Efficient Routing Protocol Avoiding Route Breaks [5] based on DSR protocol. In their work, the authors proposed a protocol to decrease the cost of link failures. It deals with avoiding route breaks by considering node and link stability. Node stability is evaluated by means of two metrics called Link Expiration Time and remaining energy. The combination of these metrics generates a measure which diminishes the cost of managing the link breakages. Stable path is established out in terms of obtained signal power strength and traffic level. Higher the value of link expiration time, higher will be the link stability. Proposed method is a modification of DSR route discovery mechanism by taking Link Stability Measure as a preemptive measure. In route discovery process, the RREQ packet carries information such as Node's Stability (NS), Traffic level (TL), Weak Node (WN) and type of data. Each node maintains a Neighbor Information Table (NIT) which stores the information like traffic level and received Power (RP). Neighbor nodes with only their traffic level  $\leq TL$  are selected. The destination selects a path with disjoint nodes. Path selection is also based on the type of data. Route maintenance is done when LSM falls below a threshold value  $LSM_{thr}$ . This protocol reduces the routing overhead as the route selection is based on traffic level and stability criterion. The selected path satisfies both energy aware and traffic load constraints and also meets the QoS objectives. Even though link breaks are reduced, delay is the main disadvantage of this approach.

Rekha Patil et al. proposed a Link Stability Based On QoS Aware On - Demand Routing for Mobile Ad Hoc Networks [11]. The task of QoS routing is to optimize the network resource consumption while satisfying the application requirements. So, there is no centralized control over links. Further the link quality varies due to mobility of nodes. Existing quality of service based routing protocols have a capacity of not making the changes in link quality once the path is generated and cost matrix is set to zero and link quality is not taken in to concern to decide the stable paths. Therefore the performance of such system degrades with high mobility. Hence in this work they stress on incorporating link quality estimation based on mobility prediction of nodes and the primary transmission path is altered in case of a get bettered route in terms of link quality is obtained. They blend the idea of link stability, cost matrix and power consumption to discover better path in terms of



both stability and cost along with QoS support. Several QoS routing protocol claims to afford best routing and packet delivery solution to MANET. the majority of these QoS techniques are node centric which denotes the time of processing route request decides if it can provide adequate QoS to path previous to forwarding route request. But variations in link quality should integrate quality of all links during which data transmission is possible. There are major factors like cost, mobility, power and energy efficiency require to be considered to guarantee better network performance. Especially while assuring QoS in MANET environment nodes must not expire due to power constraints or the links would not expire due to mobility in the middle of the transmission. So our target is to prefer a more stable path considering higher link stability and less cost along with power discrepancy. They presented a routing algorithm which achieves better in terms of cost and link quality.

The method locates the stable paths with minimum probability of link failures in the path. Power loss can also subsist a constraint for representing link stability. In this work they focused on incorporating link quality estimation based on mobility prediction of nodes incorporate same in the (AODV) routing decision to keep away from routing through the bad quality links and create new routes. The transmission path is altered to a better route in terms of link quality attained. A technique is proposed for estimating the link quality between the nodes. Each node discovers its position through the GPS (Global Positioning System). Also a unique mechanism of accumulating new path as and when a path with better link quality is accessible. The cost matrix is computed based on link stability between nodes and power is also calculated. It has some limitation random mobility of nodes with very high speed produces improper link quality measurements, multipath fading and wide channel noise changes the link quality. They have proved that, the throughput and packet delivery ratio are considerably improved in their work and control overhead is diminished to ensure better performance. There is however slight increase in latency which is attributed by more packet delivery and causes updates of layer.

#### 4. Conclusion

In this survey paper we have discussed about different energy efficient and link stability based protocols with the significance of energy efficiency and stability of links. We conclude that there is not a single protocol which can give the excellent performance in ad-hoc network when considering both the above parameters. Performance of the protocol differs according to the variation in the network parameters. Sometimes the mobility of the node of network is elevated reflecting on the node and its link stability and sometimes it is low. But energy of the node and stable links are our prime concern.

#### References

- [1] Floriano De Rango Francesca Guerriero and Peppino Fazio, "Link Stability and Energy Aware Routing Protocol in Distributed Wireless Networks," IEEE Transactions on parallel and distributed systems, vol.23, April 2012
- [2] Sunil Taneja and Ashwani Kush, "Energy Efficient, Secure and Stable Routing Protocol for MANET," Global Journal of Computer Science and Technology, Vol12, May 2012.
- [3] Floriano De Rango and Marco Fotino, "EE-OLSR: Energy Efficient OLSR routing Protocol for Mobile Ad-Hoc network," IEEE proceedings of Military communications (MILCOM'08) San Diego, CA, USA, Nov., 2008
- [4] Sachidanandh S Joshi, "Link stability Routing Protocol under Video Transmission for MANET," International Journal of Advances in Computer Networks and its Security, Vol1, Aug 2011.
- [5] Ashish Kumar, M.Q Rafiq and Kamal bansal, "Energy efficient Routing Protocol Avoiding Route Breaks based on DSR," International Journal of Computer Applications, Vol 44, April 2012.
- [6] Vinay Rishiwal, S. Verma and S.K Bajpai, "QoS Based Power Aware Routing in MANET," International Journal of Computer Theory and Engineering, Vol1, April 2009.
- [7] Priyanka Goyal, Vinti armar and Rahul Rishi, "MANET: Vulnerabilities, Challenges, Attacks, Application," IJCEM International Journal of Computational Engineering & Management, Vol. 11, January 2011
- [8] Chansu Yu, Ben Lee, Hee Yong Youn, "Energy Efficient Routing Protocols for Mobile Ad Hoc Networks," Wireless Communication and Mobile Computing, pp. 959-973, 2003
- [9] Ajit Singh, Harshit Tiwari, Alok Vajpayee and Shiva Prakash, "A Survey of Energy Efficient Routing Protocols for Mobile Ad-hoc Networks," International Journal on Computer Science and Engineering, Vol. 02, No. 09, 2010, 3111-3119.
- [10] Pinki Nayak, Rekha Agarwal, and Seema Verma, "An Overview of Energy Efficient Routing Protocols in Mobile Ad Hoc Network," International Journal of Research and Reviews in Ad hoc Networks (IJRRAN) Vol. 2, No. 1, March 2012, ISSN: 2046-5106 2012), PP 52-57.
- [11] Rekha Patil, Megha Rani.R and Rajkumar Bainoor, "Link Stability Based On QoS Aware On - Demand Routing In Mobile Ad Hoc Networks," IOSR Journal of Computer Engineering (IOSRJCE) ISSN: 2278-0661, ISBN: 2278-8727 Volume 5, Issue 3 (Sep-Oct).

#### Author Profile



**Shaik Jareena** received the B.Tech degree in computer science and Engineering from JNTU Kakinada in 2012 and pursuing M. Tech degree in Computer science and Engineering from Anurag Group of Institutions (Formerly CVSR College of Engineering) JNTU Hyderabad.



**P. Anjaiah** is working as Assistant Professor in Computer Science Engineering from Anurag Group of Institutions (Formerly CVSR College of Engineering) JNTU Hyderabad. He has received the Bachelor of Technology in Computer Science and Information Technology from Aurora's Engineering College, JNTU Hyderabad in 2004 and M. Tech in Software Engineering from School Of Information Technology, JNTU CAMPUS, Hyderabad, in 2006.