

- [7] K.Chockalingama, N.Jawahara, and U.Chandrashekar
”Influence of layer thickness on mechanical properties in stereolithography System”
- [8] Wohlers associates
- [9] alphcam-FDMTechnologies
- [10] Lee, B.H, Abdullah, J Khan , Z :Optimization of Rapid Prototyping Parameters in Production of flexible ABS object,” Materials Processing Technology Journal.
- [11] Rayegani, F, & Onwubolu, G C , Fused Deposition modeling(FDM) process parameters prediction and optimization using group method for data handling(GMDH) and differential evolution(DE).the international journal advanced manufacturing technology,2014 ,pp.1-11
- [12] Villalpando,H Eiliat, R .J Urbanic ,- An Optimization approach for components build by Fused Deposition modeling with parametric internal structures product services system and value creation. Proceedings of 6th CIRP conference on industrial product service system,800-805(2014).
- [13] S. Dinesh Kumar, V. Nirmal Kannan and G.Sankaranarayanan- Parameter Optimization of ABS-M30i part produces by fused deposition modeling for minimum surface roughness, International journal of current engineering and technology(April 2014)

Author Profile



Cany Mendonsa currently in BTech Mechanical Engineering at Manipal Institute of Technology, Manipal, Karnataka. His field of research and expertise involves machine optimization, Advanced Manufacturing System, and Rapid prototyping.



KV Naveen , currently in BTech Automobile engineering in Manipal Institute Of Technology , Manipal. Has also published article in International Journal related to Rapid Prototyping.



Prathik Upadhiaya, currently in BTech Automobile engineering in Manipal Institute of Technology, Manipal has credited paper in International Journals on Desktop Manufacturing



Vyas Darshan Shenoy, graduated from Manipal Institute Of Technology in Mechanical Engineering. He has credited to two research papers in the field of applications of Rapid Prototyping