

- [42] M.Y.A. Mollah, F. Lu, D.L. Cocke, "An X-ray diffraction (XRD) and Fourier transform infrared spectroscopic (FT-IR) characterization of the speciation of arsenic (V) in Portland cement type-V", *The Science of the Total Environment*, 224, pp. 57-68, 1998.
- [43] M.S. Mohammed, A.E. Ahmed, R.M. Osman, "Microcrystalline cellulose as a reinforcement agent to cement pastes", *Pigment & Resin Technology*, . 43(2), pp.104 – 110, 2014.
- [44] Y. Kocak, E. Tasci, U. Kaya, "The effect of using natural zeolite on the properties and hydration characteristics of blended cements", *Constr. Build. Mater.*, 47, pp. 720–727, 2013.
- [45] N.H. Rodríguez, S.M. Ramírez, M.T.B. Varela, M. Guillem, J. Puig, E. Larrotcha, J. Flores, "Re-use of drinking water treatment plant (DWTP) sludge: Characterization and technological behavior of cement mortars with atomized sludge additions. *Cem Concr Res* 2010; 40(5): 778–786.
- [46] R. Ylmén, U. Jäglid, B.M. Steenari, I. Panas, "Early hydration and setting of Portland cement monitored by IR, SEM and Vicat techniques", *Cem. Concr. Res.* 39(5), pp. 433–439, 2009.
- [47] L. Fernandez, C. Alonso, A. Hidalgo, C. Andrade, "The role of magnesium during the hydration of C₃S and C-S-H formation. Scanning electron microscopy and mid-infrared studies", *Adv. Cem. Res.* 17(1), pp. 9–21, 2005.
- [48] A.H. Delgado, R.M. Paroli, J.J. Beaudoin, "Comparison of IR Techniques for the characterization of construction cement minerals and hydrated products", *Appl. Spectrosc.* 50 (8), pp. 970–976, 1996.
- [49] M. Heikal, S. Abd El Aleem, W.M. Morsi, W.M. Characteristics of blended cements containing nano-silica", *Housing and Building Nat. Resh. Cent. J.*, 9, pp. 243–255, 2013.
- [50] J.J. Gaitero, I. Campillo, P. Mondal, S.P. Shah, "Small changes can make a great difference". *Transport Res Rec: J Transport Res Board* 2010; (2141):1–5. Transportation Research Board of the National Academies, Washington, DC.
- [51] El-Diasty Fouad, H.M. El-Said, F.I. El-Hosiny, M.I.M. Ismail, "Complex susceptibility analysis of magnetofluids: band gap and surface studies on the nanomagnetite –based powders". *Curr. Opin solid state mater Sci J.* 2009;13:28-34
- [52] Al-Khalaf, MN., Yousift, HA., "Use of the rice husk ash in concrete". *Int. J. Cem. Comp. Light Weight Concr.*, 6(4), pp. 241-248, 1984.
- [53] M.P. Ginebara, F.C.M. Driessens, J.A. Planel, "Effect of the particle size on the micro and nano-structural features of calcium phosphates cement: a kinetic analysis", *Bio-materials*, 25, pp. 3453-3462, 2004.
- [54] F. Sanchez, A. Borwankar. "Multi-scale performance of carbon microfiber reinforced cement-based composites exposed to a decalcifying environment". *Mater. Sci. Eng. A*, 527(13–14), pp. 3151–3158, 2010.

Author Profile



Dr. Ahmed A. Amer received the B.Sc, M. Sc., and Ph.D. degrees in Inorganic and Physical Chemistry, from Fac. of Science, Zagazig University, Zagazig, Egypt in 1980, 1985 and 1990, respectively. During 1980-2000, he served as a Staff member of Chemistry Department, Faculty of Science, Zagazig University, 2000-2005, a visiting professor at the Faculty of Chemical Engineering, Libya Al-Fateh University, 2005-2012 Associated Professor, Faculty of Education, King Abdul-Aziz University in Saudi Arabia, and 2012- till now, he worked as an Associated professor of Physical chemistry at the Faculty of Science (Cement technology), Zagazig University.