

# Cluster-based Protocol for Heterogeneous Wireless Sensor Networks

Neha P. Dahihandekar<sup>1</sup>, V. V. Kimbahune<sup>2</sup>

<sup>1</sup>Pune University, Smt. KashibaiNavale College of Engineering, Pune, Maharashtra, India

<sup>2</sup>Guide, Professpr, Smt. KashibaiNavale College of Engineering, Pune, Maharashtra, India

**Abstract:** *Fast growth of various applications needs the attainment of information from the physical world during a trustworthy and automatic manner. This requisite infers the emergence of latest types of networks. thus wireless detector network (WSN) has been introduced. In recent years, quick growth of wireless services and wireless devices clearly indicate potency of WSN. Utility of wireless devices is that they'll be used anyplace at any time. In WSN detector nodes area unit deployed to sense the info however these detector nodes have restricted resources which is why WSN may be a resource constraint network. so as to save lots of resources and energy, knowledge should be mass, and avoid amounts of traffic within the network. the target aggregation is to eliminate redundant data transmission and to reinforce the life time of energy in wireless detector network. economical clump schemes area unit useful for knowledge aggregation method. Thus, during this paper we tend to propose new schemes for clump with respect cluster head choice to realize energy potency and to increase the period of WSN.*

**Keywords:** Heterogeneous WSN, clustering protocols, cluster head selection, greedy algorithm.

## 1. Introduction

Wireless detector networks prove to be additional and additional helpful in acute applications, like ecological observation, good offices, field police investigation, and conveyance traffic observation. With the aim of achieving prime quality and fault-tolerant capability, a detector network is composed of tons of or thousands of detector nodes, that square measure routinely and unpredictably organized within the interested space [1] As there square measure individual nodes, there'll be probabilities of losing property of individual nodes, as a result of WSN is typically exposed to atrocious and dynamic environments. ancient centralized algorithms would like comprehensive data of the full network for operation, and if there square measure any issues in transmission or reception of packets to a node, probabilities of packet lost can occur and it'll cause a failure in protocol [2].

Quite the reverse, distributed algorithms square measure performed domestically within partial nodes, so will avoid the failure triggered by one node. Through numerous observations it's declared that localized algorithms square measure additional climbable and sturdy than centralized algorithms. The life of WSN is restricted as a result of every detector node is tightly power-constrained and. therefore there's a requirement to develop or to style energy economical protocols for prolonging life time of a network. economical arrangement of detector nodes inside clusters is helpful in reducing energy consumption.

Therefore we are able to say cluster is a vital technique to manipulate energy and topology similarly as quality and quantifiability of WSNs. There square measure clusters of detector nodes in a very clustered network. each cluster has cluster head (CH), cluster member nodes (CM). Considering numerous cluster structure [3, 4], many energy-efficient routing protocols square measure designed. These cluster protocols swish the load reconciliation and improvement the

network life. for instance, if the energy of a cluster head (CH) becomes to be unloved, another node is chosen as a CH considering some threshold.

In such some way, nodes within the network play an area in communication and networking responsibility by being CHs at completely different times. Hence, cluster enhances the network life. However, the construct of cluster remains a remarkable topic in heterogeneous or distributed WSN.

## 2. Literature Review

A. Most existing agglomeration algorithms [5-6], [7], [8] don't support heterogeneous sensors nodes. for example, well-known agglomeration protocol like LEACH [9], HEED [10] cannot manage sensing element nodes a lot of expeditiously with regard to energy consumption. Thus, there's a requirement to style energy economical agglomeration protocol for distributed WSN by that specialize in well-organized cluster head (CH).

B. Various authors have studied and implemented various protocols such as, Smaragdakis et al [11] and dynasty, D [12] have studied the influence of nonuniformity of sensing element nodes, in terms of their energy and heterogeneous-aware protocol to increase the quantity before the death of the primary node, that is crucial for numerous applications wherever the response from the sensing element network should be trustworthy. Gupta et al [13] conferred a cluster head choice technique victimisation mathematical logic to beat the defects of LEACH. however this investigation is helpful in in consistent network system victimisation fuzzy variables.

In this paper, we've well thought-out 3 forms of sensing element node. Some section of the sensing element nodes area unit fortified with the value-added energy resources than the opposite nodes. We have assumed that each one the sensing element nodes area unit uniformly distributed.

within the Heterogeneous WSN, we tend to projected energy economical cluster head choice protocol and victimization the greedy approach to construct Associate in Nursing put down cluster routing

### 3. Proposed Work

To overcome limitations of existing clump technique, associate innovative economical clump protocol should be offered. during this paper, we've thought of 3 sorts heterogeneous sensing element nodes. Assumed that every one the sensing element nodes square measure equally distributed having some speak time(T), residual energy(RE) and having initial energy(IE). In the Heterogeneous WSN, a projected is for associate energy economical cluster head choice protocol exploitation greedy approach to construct associate inter-cluster routing.

#### A. Proposed scheme

New proposal prompt that, let there area unit 3 kinds of nodes in heterogeneous WSN, consisting of various initial energy (node\_type1, node\_type2, node\_type3 with initial energy IE1 IE2 and IE3 respectively). The nodes establish themselves into native clusters, with one node which can be ab initio acting because the Cluster Head (CH). All non-cluster-head nodes should pass away their knowledge to the cluster head, and this collected knowledge from cluster members ought to be gathered and processed by cluster head node to the remote base station. Hence, being a cluster head node is far additional energy-rigorous than being a non-cluster-head node.

In cluster set-up part, we tend to offer every node a talk-time (T) per its residual energy. The regulation is, the additional residual energy, the less time of its talk-time. Henceforth, node with additional residual energy has less time than node with less residual energy. Throughout this era, nodes that get messages from alternative nodes can opt for it's a non-cluster head.

Meanwhile the cluster head node identifies all the cluster members; it deeds as native management centers to synchronize the information transmissions within the cluster. The cluster head node establishes a TDMA schedule and conveys this schedule to the nodes within the cluster. This safeguards that there aren't any collisions between information messages and additionally sanctions the radio parts of every non-cluster-head node to be converted in the slightest degree times except throughout their transmit time, therefore energy dissipation by the individual sensors is decreased .

With the aim of reducing the energy consumption of the cluster heads that area unit remote from BS and equalization the energy consumption of the cluster heads that area unit adjacent to BS, a multiple-hop routing algorithmic program of cluster head and greedy approach area unit introduced, that contribute to seek out the residual energy, with relation to talk time.

#### B. Cluster Head Selection

Most of the organized results of previous analysis ar gained forward that the nodes of the device network ar armed with the identical quantity of energy. however this can be not the case, therefore during this paper, influence of heterogeneousness in terms of node energy is introduced. Let develop a model for a WSN with nodes heterogeneous in sorts of nodes within the device field with not like energy (node\_type1, node\_type2, node\_type3).

Let node\_type1, node\_type2 ar having  $\alpha$  and  $\beta$  times additional energy than node\_type3. And P1 and P2 ar the proportion of node\_type1 and node\_type2 within the nodes set. impromptu, node\_type1 and node\_type2 need to become cluster heads: additional oftentimes than node\_type3. clearly new heterogeneous setting has improved the overall initial energy of the network. Assume, IE1 IE2 associated IE3 ar an initial energy of node\_type1, node\_type2, node\_type3 resp. It is given by,

$$\begin{aligned} IE_1 &= IE_3(1+\alpha) \quad (1) \\ IE_2 &= IE_3(1+\beta) \quad (2) \end{aligned}$$

Therefore, the whole initial energy of the new heterogeneous network is equal to:

$$E_{tot} = n(1-P_1-P_2)IE_3 + nP_1IE_1 + nP_2IE_2 \quad (3)$$

The steady region of the sensing element network is improved by (1+Q) times. That is, (1) every node\_type3 node becomes a cluster head once each (1+Q)/  $P_{optimum}$  rounds per CH; (2) every node\_type1 node becomes a cluster head precisely (1+ $\alpha$ ) times each (1+Q)/  $P_{optimum}$  round per CH; (3) every node\_type2 node becomes a cluster head precisely (1 + $\beta$ ) times each (1 +Q)/  $P_{optimum}$  rounds per CH. Thus, the optimum choice proportion of each node is:

$$\begin{aligned} P_{n1} &= P_{optimum} / (1+Q) * (1+\alpha) \\ P_{n2} &= P_{optimum} / (1+Q) * (1+\beta) \\ P_{n3} &= P_{optimum} / (1+Q) \end{aligned}$$

#### C. Cluster Setup

Every non-cluster-head node that's a cluster member (CM) defines to that cluster it belongs by choosing the cluster head with the utmost residual energy, which desires the smallest amount communication energy, supported the received signal strength of the advertising from every cluster head.

Initially all cluster members figure the approximate distance d between the sender nodes and itself supported the received signal strength.

Every node decides to that cluster it belongs by the utmost Cassis. afterward the node notifies the cluster head node that it'll be a member of the cluster. every node transmits Associate in Nursing assist request message back to the electoral cluster head. This message may be a very little message, consisting of the node's ID and therefore the cluster head's ID. as a result of the cluster head nodes consume their energy quicker than different nodes, we have a tendency to should elect some subordinate cluster head (subordinate -CH) nodes to help the cluster head's work.

The confirmation message contains the residual energy Eresidual of this CM node. each cluster head node types downward by Eresidual and elects the highest y stronger nodes because the subordinate -CH nodes. These subordinate -CH nodes assist the cluster head to gather, mixture the data and allot tasks to different nodes.

- 1) The cluster head node is numbered No. 1 CH node, different y stronger subordinate-CH area unit numbered No. 2, . . . , No.(x+ 1) nodes in incline order by Eresidual.
- 2) The cluster heads deed as native management centers to help the information transmissions in their cluster.
- 3) The CH node establishes a TDMA schedule and transmits this schedule to the nodes within the cluster.
- 4) This confirms that there aren't any collisions among knowledge messages.
- 5) The approach of exploitation the association of cluster head and subordinate CH nodes improves energy potency and elongates the system period of time.

#### 4. Conclusion

In this paper, associate introduction to associate energy economical cluster head election methodology to construct associate inter-cluster routing within the heterogeneous WSN is place up. And economical use of greedy approach that's use program to implement multiple-hop, short distance communication among the CH and baccalaureate, associated notice an optimum short-distance path within the cluster head's communication. Therefore this recently introduced technique for heterogeneous WSN is a lot of economical than existing techniques and may be helpful for prolonging life time of a network.

#### References

- [1] F. Akyildiz, W. Su, Y. Sankarasubramaniam, E. Cayirci, A survey on sensor networks, IEEE communications magazine 40 (8) (2002) 102–114.
- [2] L. Karim, N. Nasser, and T. Sheltami. A fault tolerant dynamic clustering Protocol of wireless sensor networks. In Global Telecommunications Conference, 2009.GLOBECOM, pages 1- 6, 30 Nov - Dec 4 2009.
- [3] P. Krishna, N.H. Vaidya, M. Chatterjee, D. Pradhan, A cluster-based approach for routing in dynamic networks, ACM
- [4] B. McDonald, T. Znati, Design and performance of a distributed dynamic clustering algorithm for Ad-Hoc networks, in: Proceedings of the Annual Simulation Symposium, 2001.
- [5] F. Bajaber and I. Awan, "Dynamic/Static Clustering Protocol for Wireless Sensor Network," Computer Modeling and Simulation, 2008.EMS '08.SecondUKSIM European Symposium on, pp. 524-529, 2008.
- [6] Heinzelman, W.R.; Chandrakasan, A.; Balakrishnan, H. Energy-Efficient Communication Protocol for Wireless Microsensor Networks. In Proceedings of the 33rd Annual Hawaii International Conference on System Sciences, Maui, HI, USA, 4–7 January 2000; pp. 10–19.

- [7] Younis, O.; Fahmy, S. HEED: A hybrid, energy-efficient, distributed clustering approach for ad-hoc sensor networks. IEEE Trans. MobileComput.2004, 3, 366–379.
- [8] Smaragdakis,G., Matta, I. and Bestavros, A. 2004 SEP: A Stable Election Protocol for clustered heterogeneous wireless sensor networks. In Proceedings of Second International Workshop on Sensor and Actor Network Protocols and Applications (SANPA 2004), Boston, MA, August.
- [9] Wei, D. , Kaplan, S. and Chan H .A. 2008 Energy Efficient Clustering Algorithms for Wireless Sensor Networks. In Proceedings of IEEE Communications Society (ICC 2008), pp.236-240.
- [10] Park, S.H.,Cho, J.S, Han,Y.1. andChung,T.M. 2007 Architecture of Context Aware Integrated Security Management Systems for Smart Home Environments. APNOMS2007, LNCS 4773, October, pp.543-546.