Erection Trusted and Effective Request Services in the Cloud with RASP Data Perturbation

Rashmi Kadu¹, Sonali Patil²

¹ME CSE- Final Year, BSIOTR Wagholi (Pune), Maharashtra, India

²Assistant Professor, CSE Dept, BSIOTR Wagholi (Pune), Maharashtra, India

Abstract: Cloud computing infrastructure madeinformation accessible to public which has become an appealing solution for the advantages on scalability and cost-saving. However, some data is so sensitive that the data owner does not want to move to the cloud unless the data confidentiality and query privacy are guaranteed. The RASP data perturbation method provides secure and efficient range query and kNN query services for protected data in the cloud. The kNN-R algorithm works with the RASP range query algorithm to process the kNN queries. The nearest neighbours concept involves interpreting each entry in the database as a point in space. k Nearest Neighbours (kNN) algorithm selects k entries which are closest to the new point. However kNN algorithm performs slowly on large databases since each new entry has to be compared to every other entry. There is a alternative method proposed which is fit to the large sized databases. This method is FCNN i.e. fast condensed nearest neighbour data reduction method. In this method the database is summarized by finding only the important data points. The main purpose of this method is to approximate the nearest neighbour algorithm, 1NN, with a smaller, more representative set of data points.

Keywords: Cloud Computing, RASP, security, FCNN algorithm

1. Introduction

While using the exiting services of cloud computing, the growing concern is how to store, manage, and analyze a large volume of data while preserving the privacy [6]. The RAndom Space Perturbation (RASP) approach is used to construct practical range query and k-nearest-neighbor (kNN) query services in the cloud. The RASP perturbation is a unique combination of OPE i.e. order preserving encryption, dimensionality expansion, random noise injection, and random projection, which provides strong confidentiality guarantee [1] [5]. In FCNN several training set condensation algorithms have been introduced, also known as instance-based, lazy, memory- based, and casebased learners. These methods can be grouped into three categories depending on the objectives that they want to achieve competence preservation, competence enhancement, and hybrid approaches. The goal of competence preservation methods is to compute a training set consistent subset removing superfluous instances that will not affect the classification accuracy of the training set. Competence enhancement methods aim at removing noisy instances in order to increase classifier accuracy. Finally, hybrid methods search for a small subset of the training set that, simultaneously, achieves both noisy and superfluous instances elimination. Competence enhancement and preservation methods are combined in order to achieve the same objectives of hybrid methods [3].

2. Literature Survey

Title 1: RASP-QS: Efficient and Confident Query Services in the Cloud

Author of this paper Zohreh Alavi, Lu Zhou, James Powers, Keke Chen studied that data perturbation allows user to select one of the datasets. The perturbation parameters have to be generated OPE parameters are dataset-specific and the size of matrix A is subject to the dimensionality of the dataset. The perturbated data is sent to the server. The server then conducts multidimensional indexing on the perturbated data space. This demonstration shows a prototype for efficient and confidential range/kNN query services built on top of the random space perturbation (RASP) method. The RASP approach provides a privacy guarantee practical to the setting of cloud based computing, while enabling much faster query processing compared to the encryption-based approach. This demonstration will allow users to more intuitively understand the technical merits of the RASP approach via interactive exploration of the visual interface [4]. The main purpose of this demonstration is to show the key ideas of the RASP-based query processing approach for efficiently and confidentiality hosting query services in the cloud.

Title: Fats Condensed Nearest Neighbor Rule

Author of this paper Fabrizio Angiulli presents a novel algorithm for computing a training set consistent subset for the nearest neighbor decision rule. The algorithm, called FCNN rule, has some desirable properties. Indeed, it is order independent and has sub- quadratic worst case time complexity, while it requires few iterations to converge, and it is likely to select points very close to the decision boundary. [3] The comparison took place between the FCNN rule with state of the art competence preservation algorithms on large multidimensional training sets, showing that it outperforms existing methods in terms of learning speed and learning scaling behavior, and in terms of size of the model, while it guarantees comparable prediction accuracy. This paper presented a novel order independent method for computing a training set consistent subset for NN rule and compared it with existing state of the art competence preservation method. The observed superior learning speed of the new method is substantiated by the learning behavior comparison. This work can be extended in

several ways, e.g. studying the impact of different metrics on the FCNN rule and the behavior of FCNN- based hybrid method.

3. Existing System

Random space perturbation (RASP) approach to constructing practical range query and knearest-neighbor (kNN) query services in the cloud. The RASP kNN query service (kNN-R) uses the RASP range query service to process kNN queries. The nearest neighbours approach involves interpreting each entry in the database as a point in the neighbours are taken from a set of objects for which the class or the object property value is known. The nearest neighbours approach involves interpreting each entry in the database as a point in space. Then, the similarity of two points is measured by the distance between them. The nearest neighbours approach then classifies the new sample by looking at the classifications of those closest to it. In the k Nearest Neighbours (kNN), this is achieved by selecting the k entries which are closest to the new point. The best choice of k depends upon the data. Generally, large values of k reduce the effect of noise on the classification [7]. The accuracy of the kNN algorithm can be degraded by the presence of noisy or irrelevant the features, or if the feature scales are not consistent with their importance. When the input data to an algorithm is too large to be processed and it is suspected to be notoriously redundant (e.g. the same measurement in both feet and meters) then the input data will be transformed into a reduced representation set of features (also named features vector). Transforming the input data into the set of features is called feature eta in order to extraction. If the features extracted are carefully chosen it is expected that the features set will extract the relevant information from the input data in order to perform the desired task using this ion reduced representation instead of the full size input. Feature extraction is performed on raw data prior to applying k-NN algorithm on the transformed data in feature space [8].

4. Proposed System

A. Fast Condensed Nearest Neighbours (FCNN)Data Reduction

Data Reduction: The database is summarized by finding only the important data points. Data points in the training set are divided into three types [3], Outliers, Prototypes, Absorbed. The purpose of this method is to be able to approximate the nearest neighbour algorithm, 1NN, with a smaller, more representative set of data points.

- Outliers are points whose k nearest points are not of the same class.
- $X=\{x1, x2,..., xn\}$ (without outliers) $P=\{x1\}$
- We scan all elements of X and move individual elements to P if their nearest prototype (their nearest element from P) has a different class label
- Repeat until no more new prototypes are found.

Properties of CNN

- Absorbed points are the points which are not prototypes.
- CNN reduces the amount of data necessary for classification.

• Points are labelled as either prototypes, outliers or absorbed points.

• Absorbed points and outliers are then no longer used in classification tasks, validation tests or maps of the data set.

B. Algorithm

Algorithm FCNN (T: training set)

- 1) Initialize the set S to the empty set
- 2) Initialize the set ΔS to the set Centroids (T)
- 3) While the set ΔS is not empty:
- 4) Augment the set S with the set Δ S
- 5) Initialize the set ΔS to the empty set
- 6) For each object y in the set S, insert into ΔS the representative object of the Voronoi enemies of y in the T w.r.t S
- 7) Return the set S

5. System Architecture

Each record x in the outsourced database contains two parts: the RASP-processed attributes

D' = F(D,K) and the encrypted original records, Z = E(D,K'), where K and K' are keys for perturbation and encryption, respectively. The RASP-perturbed data D' are for indexing and query processing [2]. There are a number of basic procedures in this framework [5]:

- 1) F(D) is the RASP perturbation that transforms the original data D to the perturbed data D';
- 2) Q(q)transforms the original query q to the protected form q' that can be processed on the perturbed data;
- 3) H(q',D') is the query processing algorithm that returns the result R'.

Figure 1 shows the system architecture for both RASP-base range query service and kNN service.



Figure 1: System Architecture of RASP

6. Modules

A. User Module

In this module, Users are having authentication and security to access the detail which is presented in the ontology system. Before accessing or searching the details user should have the account in that otherwise they should register first.

B. Dimensional Reduction

Dimensional are derived from R-tree like algorithms, where the axis-aligned minimum bounding region (MBR) is the

Volume 4 Issue 6, June 2015 www.ijsr.net

construction block for indexing the multidimensional data. For data, an MBR is a rectangle. For higher dimensions, the shape of MBR is extended to hyper-cube. The MBRs in the R-tree for a dimensional dataset, where each node is bounded by a node MBR. The R-tree range query algorithm compares the MBR and the queried range to find the answers.



Figure 2: Dataflow Diagram

C. Performance of FCNN Rule Processing

In this set of experiments, we investigate several aspects of CNN query processing.

- 1) We will study the cost of (n, δ) -Range algorithm, which mainly contributes to the server-side cost.
- 2) We will show the overall cost distribution over the cloud side and the proxy server.
- We will show the advantages of FCNN over another popular approach: the Casper approach for privacypreserving FCNN search.

D. Preserving Query Privacy

Private information retrieval (PIR) tries to fully preserve the privacy of access pattern, while the data may not be encrypted. PIR schemes are normally very costly. Focusing on the efficiency side of PIR, Williams et al. use a pyramid hash index to implement efficient privacy preserving datablock operations based on the idea of Oblivious RAM. It is different from our setting of high throughput range query processing. Hu et al. addresses the query privacy problem and requires the authorized query users, the data owner, and the cloud to collaboratively process FCNN rules. However, most computing tasks are done in the user's local system with heavy interactions with the cloud server. The cloud server only aids query processing, which does not meet the principle of moving computing to the cloud.

7. Results

A. Input Given

Problem Definition

A training database which trains us to know what the different types of things look like.We are having a database of the characteristics land admin, state, country, landmark,

facility. Then we will take a new sample and want to know what classification it should be. The classification is based on the items of the training database, the new sample is similar to Aim is to use this database to give a new person a perfect landmark and facility. Again, we want to classify it with the type of landadmin it is most similar to.

Requirement:

1) Database Creation:

We start with a database of objects who's classification we already know.

The datasets, "Hospitals.csv, Rest.csv, Toll Transaction.csv" are taken from

UCI repository. The website of UCI Repository is http://archive.ics.uci.edu/ml/

The UCI Machine Learning Repository is a collection of databases, domain theories, and data generators that are used by the machine learning community for the empirical analysis of machine learning algorithms. This repository currently maintain 308 data sets as a service to the machine learning community.

2) Origin:

This dataset was taken from the StatLib library which is maintained at Carnegie Mellon University.

3) Creator:

Harrison, D. and Rubinfeld, D.L.

'Hedonic prices and the demand for clean air', J. Environ. Economics& Management, vol.5, 81-102, 1978.

Data Set Characteristics:	Multivariate	Number of Instances:	506	Area:	NA
Attribute Characteristics:	Categorical, Integer, Real	Number of Attributes:	14	Date Donated	1993-07-47
Associated Tasks:	Regression	Missing Values?	No	Number of Web Hits:	128761

Figure 3: Database specification

3) Data Set Information:

The database used in this project contains concerns housing values in suburbs of Boston

Software Requirement:

1) WampServer:

WampServer is a Windows web development environment. It allow to create web applications with Apache2, PHP and a MySQL database. Alongside, PhpMyAdmin allows to manage database easily.

2) MySQL:

The MySQL development project has made its source code available under the terms of the GNU General Public License, as well as under a variety of proprietary agreements. Free-software-open source projects that require a full-featured database management system often use MySQL. MySQL is also used in many high-profile, largescale World Wide Web products, including Wikipedia, Google (though not for searches), Facebook, and Twitter.

International Journal of Science and Research (IJSR) ISSN (Online): 2319-7064 Index Copernicus Value (2013): 6.14 | Impact Factor (2013): 4.438

ad							
					Г		
e setsio	ecLocabor1	24	Load	Extract		View	Next
	NY 879781		-				100111
ew Dat	aset						
landmin	statelp	countryfo	landmark	facilityid	link,	4444	
379674	33	13	Pine Ground _	27076	28		
340058	29	51	Steeley Critity	1743	18.		
514836	42	91	St Mary s Sch.	27597	28		
391562	34	37	Don Bosco C	2843	29.		
34,7063	42	35	Marcrest Cir	28798	30.	_	
200000	1.00	01	Hidden Valley	31171	34.		
515188	42						
515188	42 6	37	Public Elem	7710	79.		
515188 46283 410465	42 6 36	37 47	Public Elem Rutand Placa	7710 37250	79. 54		
515188 48203 410455 41638	42 6 36 6	37 47 25	Public Elem Rultand Placa Dearca Elem	7710 37250 14626	79. 54. 15.		
515188 46203 410455 41638 599601	42 6 36 6 49	37 47 25 36	Public Elem Rutland Placa Deanca Elem S Weymouth	7710 37250 14626 20578	79. 54. 15. 29.		
515188 46283 410455 41638 599601 267746	42 6 36 6 49 24	37 47 25 36 5	Public Elem Rutland Placa Dearca Elem S Weymouth Devonshire F	7710 37250 14626 29578 19213	79. 54. 15. 29. 19.	1000	
515188 46283 410455 41638 599601 267746 349516	42 6 36 6 49 24 29	37 47 25 36 5 173	Public Elem Rutland Placa Deanca Elem S Weymouth Devonative F Rate	7710 37250 14626 28678 19213 3010	79. 54. 15. 29. 19. 31.		
515188 48283 410455 41638 589601 267746 349516 48234	42 6 36 6 49 24 29 6	37 47 25 36 5 173 37	Public Elem Rutland Placa Deanta Elem S Weymouth Devonshire F Raits County Heat	7710 37250 14525 20578 10213 3010 22320	79. 54. 15. 29. 19. 31. 23.		
515188 44283 410455 41038 599601 267746 349516 49234 410382	42 6 36 6 49 24 29 6 36	37 47 25 36 5 173 37 47	Public Elem Rattand Placa Dearca Elem S Weymouth Devonshire F Ratts County Heatt. Plar 12	7710 37250 14525 20578 10213 3010 22320 6051	79. 54. 15. 29. 19. 31. 23. 62.		
515188 46283 410455 589601 287746 48224 410382 48224 410382 341971	42 6 36 6 49 24 29 6 36 29	37 47 25 38 5 173 37 47 77	Public Elem Rutland Placa Dearca Elem S Weymouth Devonitive F Rafis County Heatt. Pier 12 Mumford	7710 37250 14526 28578 19213 3010 22320 6051 25615	79.54.15.29.19.31.23.62.26.26.26.26.26.26.26.26.26.26.26.26.		

Figure 4: Viewing a Dataset

B. Output Observed

Table 1: Comparison of Nearest Neighbour Techniques

Sr No	Technique	Key Idea	Advantages	Disadvantages	Target Data
1	K nearest Neighbor (kNN) [8]	Uses nearest neighbor rule	1. training is very fast 2. Simple and easy to learn 3. Robust to noisy training data 4.Effective if training data is large	Biased by value of k Computation Complexity Memory limitation d. Being a supervised learning lary algorithm i.e. runs slowty S. Easily fooled by irrelevant attributes	large data samples
2	Condensed nearest neighbor (CNN) [9,10,11]	Eliminate data sets which show similarity and do not add extra information	1. Reduce size of training data 2. Improve query time and memory requirements 3.Reduce the recognition rate	1. CNN is order dependent; it is unlikely to pick up points on boundary. 2. Computation Complexity	Data set where memory requirement is main concern

Performance of KNN:

- In order to investigate how good the initial training set is, a procedure called cross validation gets used.
- This involves running the kNN algorithm on each of the points in the training set in order to determine whether they would be recognized as the correct type
- It can clearly be seen that including more random noise points in the training set increases the number of cross validation errors
- As the number of random noise points becomes very large, the percentage of points which
- fail the cross validation tends to 50%



Figure 5: Performance of kNN algorithm

Problems with kNN:

Average Number of Errors

- kNN algorithm is difficult to implement for some datatypes. This is because it relies on being able to get a quantitative result from comparing two items
- Slow for large databases: Since each new entry has to be compared to every other entry

Performance of FCNN algorithm:

- Classifying a new sample point is now faster, since we don't have to compare it to so many other points.
- This is the trade of we have to make, between speed and accuracy is better than kNN algorithm. Percentage of points classed as outliers increased dramatically.
- Percentage of points classed as absorbed decreased.
- Percentage of points classed as prototypes increased slightly



Figure 7: Performance of FCNN algorithm



Figure 6: Application Homepage

	Client Regions		POI -3 Reg	ions
Region 1	Region 2 Lattitude	Regions	Lattitude	Longitude 🔺
10000	Dunbar-Broadway	HMB	39.5678	76.0731
10000	garffgfhbn 39,5892	JFK	39,5892	76.0728
10000	Mount Vernon 38.3647	HWN	38.3647	76.9761
10000	Penrose-Favette Street Out	FMT	39.2661	76.6158
10000	Levindale 39.2305	FSK	39.2305	76.5107
10000	Middle Branch/Reedhird Par	BHT	39.2406	76.5872
1	•	HWN	38.3647	76.9761
		FSK	39.2305	76.5107
	POI-1 Regions		POI-2 Keg	ions
Regions	Lattitude Longitude 🔺	Regions	Lattitude	Longitude 🔺
DINGHOW	RESTAURANT 39.2886	John Hopki	ns Hospital	39.2975
DIONYSUS	RESTAURANT&LOUNGE	Maryland G	eneral Hospital	39.006
DIZZYIZZY	39.329 76.6336	Bon Secour	s Hospital	39.2953
DOMINICA	NOINTERNACIONAL	Harbor Hos	pital Center	39.2866
DOMINOSU	GARCAFATERIAOPERATION	St. Agnes H	ospital	39.3455
DONNAS	39.2953 76.6212 -	Union Mem	orial Hospital	39.2295
		C 1 C	itan Hospital	30 2840
•	•	Good Sama	itan nospitai	J7.2047

Figure 8: Extracting the Regions

1 Step 2 Step 3						
Regions	Neighboring Regions	Spatial Distance				
Dunbar-Broadway	indira gandhi internatio	31.265	٠			
garffgfhbn	indira gandhi internatio	31.268		_		
Mount Vernon	indira gandhi internatio	31.987				
Penrose-Fayette Street	indira gandhi internatio	31.753				
Levindale	indira gandhi internatio	31.644			_	
Middle Branch/Reedbir	indira gandhi internatio	31.721				
Violetville	indira gandhi internatio	31.987		NN-3		
Charles Village	indira gandhi internatio	31.644		111-5		
Loch Raven	indira gandhi internatio	31.265				
Hopkins Bayview	indira gandhi internatio	31.509				
HolabirdIndustrialPark	indira gandhi internatio	31.268				
FederalHill	indira gandhi internatio	31.7				
FellsPoint	indira gandhi internatio	31.721		Update-3		
WashingtonVillage	indira gandhi internatio	31.987		<u>k</u>		
Mid-Govans	indira gandhi internatio	31.265				
CentralForestPark	indira gandhi internatio	31.716				
MorrellPark	indira gandhi internatio	31.7				
CoppinHeights/Ash-Co	indira gandhi internatio	31.509				
InnerHarbor	indira gandhi internatio	31 509	•			

Figure 9: Calculate Distance Using NN-3 Algorithm

Minimum	10.064		Maximum 10.695	
	Set Threshold Value	10.085	submit	
region	region	1	distance	
Dunbar-Broadwa	y SIRSA		10.064	
Dunbar-Broadwa	W SIRSA		10.054	
gailighbn	SIRSA		10.085	
garfighbn	SIRSA		10.085	
Levindale	HISSA	R	10.08	
Levindale	HISSA	R	10.08	
Charles Village	HISSA	R	10.08	
Charles Village	HISSA	R	10.08	
Loch Raven	SIRSA		10.064	
Loch Raven	SIRSA		10.054	
Holabirdindustria	iPak SRSA		10.085	
Holabirdindustria	iPark SRSA		10.085	
FellsPoint	HISSA	R	10.08	
FellsPoint	HISSA	R	10.08	
FellsPoint	HISSA	R	10.08	
WashingtonVilla	IN SIRSA		10.054	
WashingtonWilay	e SRSA		10.064	
WashingtonWilay	IN SIRSA		10.064	
Mit Change	9894		10.064	

Figure 10: Calculate Distance Using Range Query

Select the Number of Centroids	4	submit	
Centroids	10.06399999999999988,1	0.063999999999999	
Find the Nearest Neighbors		Find	
region1	region2	distance	
region1 303-Authority-Drive-altimore	region2 SIRSA	distance 10.064	1
region1 303-Authority-Drive-altimore 6000-Pulaski-Highway-Perryville	region2 SIRSA SIRSA	distance 10.064 10.064	
region1 303-Authority-Drive-altimore 6000-Pulaski-Highway-Perryville Hampden	region2 SIRSA SIRSA SIRSA	distance 10.064 10.064 10.064	
region1 303-Authority-Drive-altimore 6000-Pulaski-Highway-Perryville Hampden Downtown	region2 SIRSA SIRSA SIRSA SIRSA	distance 10.064 10.064 10.064 10.064	
region1 303-Authority-Drive-altimore 6000-Pulaski-Highway-Perryville Hampden Downtown MountiVernon	region2 SIRSA SIRSA SIRSA SIRSA SIRSA	distance 10.064 10.064 10.064 10.064 10.064	
region1 303-Authority-Drive-altimore 6000-Pulaski-Highway-Perryville Hampden Downtown Nounfi/emon InnerHarbor	region2 SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA	distance 10.064 10.064 10.064 10.064 10.064 10.064	
region1 303-Autority-Drive-altimore 6000-Pulaski-Highway-Perryville Hampden Downtown Mount/Vernon InnerHatbor Niid-Govans	region2 SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA	distance 10.064 10.064 10.064 10.064 10.064 10.064 10.064	
region1 303-Authorly-Drive-altimore 6000-Pulasixi-Highway-Perryville Hamgden Downtown Mount/vernon InnerHarbor Mid-Govans WashingdonVillage	region2 SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA	distance 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064	
region1 303-Aufborth-Drive-altimore 6000-Pulaski-Hiphway-PernyNile Hampden Downtown Mount/vernon InnerHarbor Mid-Gorans Washington/Nilage Loch Raven	region2 SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA	distance 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064	
region1 303-Authorthy-Drive-altmore 6000-Pulasti-Highway-Perryville Hampden Downtown Mount/vernon InnerHatbor Mid-Gorans WashingtonVillage Loch Raven Durbat-Broadway	region2 SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA	distance 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064	
region1 303-Authordy-Drive-attimore 6000-Pulash-Highway-Pernyille 6000-Pulash-Highway-Pernyille Downtown Mount/vernon InnerHarbor Mid-Gorans Washington/illage Loch Raven Dunbar-Broadway 303-Authordy-Drive-attimore	region2 SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA	dstance 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064	
region1 303-Authorth-Drive-allmore 6000-Pulasti-Highwai-Perrytile Hampden Downtown Nount/remon InnerHatbor Mid-Covans Washington/Wlage Loch Raven Dunbar-Broadway 303-Authorth-Drive-allmore 6000-Pulasti-Highwai-Perrytile	region2 SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA	distance 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064	
region1 300-Authordy-Dhive-attimore 6000-Pulaask-Highway-Pernyille Hampden Downtown Mount/vernon InnerHarbor Mid-Gonans Washingdon/Wage Lock Reven Dunbas-Broadway 303-Authordh-Ohre-attimore 6000-Pulaask-Highway-Pernyille Hampden	region2 SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA	dstance 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064	
region1 303-Authordy-Drive-attimore 6000-Pulasist-Highway-Pernyille Hampdan Downtown Mo-Goaras Mid-	region2 SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA SIRSA	distance 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064 10.064	
region1 200-Authordy-Dhue-attimore 6000-Pulaasit-Highway-Pernyille Hampdon Downtown Mount/erronn InnerHarbor Mid-Gorans Washington/Wage Loch Raven Dumba-Proceadway 303-Authordy-Dhue-attimore 6000-Pulaasit-Highway-Pernyille Hampdon Downtown Mount/erronn	region2 SIRSA	dstance 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064	
region1 303-Authordy-Drive-attimore 6000-PulasisH-Biptway-Pernyille Hampdan Downhown Mount/emon Inde-Karabor Mid-Socaris S Washington/illage Loch Raven Dunhar-Broadway 303-Authordy-Drive-attimore 6000-PulasisH-Biptway-Pernyille Obudhar Bintonet Hampdan Downtown Mount/ternon InnerHarbor	region2 SIRSA SIRSA	dstance 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064	
region1 303-Authordy-Dhue-attimore 6000-Pulaasik-Highway-Pernyille Hampden Downtown Mid-Gorans Washington/Wage Loch Raven Dumbar-Broadway 303-Authordy-Dhue-attimore 6000-Pulaasik-Highway-Pernyille Hampden Downtown Mid-Gorans	regim2 SIRSA	dstance 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064 10064	

Figure 11: Distance calculation Using FCNN Algorithm

Client_Final_Page		- 🗆 X
/Recommended_owner	Road Details	
Airport Name	SIRSA	
Address Line 1	8987 ft	Map
Current Pacition	10.064	Comparison
	C	





Figure 13: Comparison between KNN, Range Query and FCNN

8. Conclusion

RASP aims to preserve the topology of the queried vary in the rattled area, and permits to use indices for efficient vary question process. With the topology-preserving features, one can develop economical vary question services to realize sub. kNN classifies unknown instances based on a majority vote of the k nearest examples from the training set. The most frequent class label amongst these k nearest examples is then assigned to our unknown instance. Where as in CNN, the condensed nearest neighbour rule for data reduction, The database is summarized by finding only the important data points. It reduces the data set to a condensed data set. It labels points as either prototypes, outliers or absorbed points. Only prototypes are used in classification tasks, validation tests and maps, as they are considered to be more or less representative of all of the points in the initial data set. The performance of FCNN is better than kNN for large dataset as it find out prototypes first and then perform kNN algorithm later.

References

- [1] B. Wang, B. Li, and H. Li, "Public Auditing for Shared Data with Efficient User Revoation in the Cloud," *in the Proceedings of IEEE INFOCOM2013, 2013, pp. 2904–2912.*
- [2] M. Armbrust, A. Fox, R. Griffith, A. D. Joseph, R. H. Katz, A. Konwinski, G. Lee, D. A. Patterson, A. Rabkin, I. Stoica, and M. Zaharia, "A View of Cloud Computing," *Communications of the ACM*, vol. 53, no. 4, pp. 50–58, Apirl 2010.
- [3] F. Anguilli, Fast Condensed Nearest Neighbor Rule. Proceedings of the 22nd International Conference on Machine Learning, Bonn, Germany, 2005.
- [4] Zohreh Alavi, Lu Zhou, James Power, Keke Chen, "RASP-QS: Efficient and Confidential Query Services in the Cloud", Proceedings of theVLDB Endowment, Vol. 7, No. 13
- [5] C.Wang,Q.Wang,K.Ren,andW.Lou, "Privacy-Preserving Public Auditing for Data Storage Security in Cloud Computing"
- [6] Huiqi Xu, Shumin Guo, Keke Chen, "Building Confidential and Efficient Query Services in the Cloud with RASP Data Perturbation" *Knowledgeand Data Engineering, IEEE Transactions on (Volume:26, Issue: 2)*
- [7] Everitt,B.S.,Landau,S.,Leese,M. and Stahl, D. (2011),
 "Miscellaneous Clustering Methods, in Cluster Analysis",
 5th Edition, John Wiley & Sons,Ltd, Chichester, UK
- [8] Cover TM, Hart PE (1967). "Nearest neighbor pattern classification". *IEEE Transactions onInformation Theory*.
- [9] T. M. Cover and P. E. Hart, "Nearest Neighbor Pattern Classification", *IEEE Trans. Inform.Theory, Vol. IT-13, pp* 21-27, Jan 1967.
- [10] K. Chidananda and G. Krishna, "The condensed nearest neighbor rule using the concept of mutual nearest neighbor", *IEEE Trans. InformationTheory, Vol IT- 25 pp.* 488-490, 1979.
- [11] F Angiulli, "Fast Condensed Nearest Neighbor", ACM International ConferenceProceedings, Vol 119, pp 25-32