











flows but can be successfully applied for the supersonic and hypersonic flows. A good match has been found between CFD results and the L1D results.

## References

- [1] Al-Falahi, A. M.Z. Yusoff, Shauib N.H, T. Yusaf Flow instability in shock tube due to shock wave boundary layer contact surface interactions, a numerical study. *European journal of scientific research*, ISSN 1450-216X vol. 30 No.1
- [2] Blazek, J. (2001). *Computational Fluid Dynamics Principal and Applications*. *Eselvier*.
- [3] Liou, M. S. and C. J. Steffen (1999). A New Flux Splitting Scheme. *Journal of Computational Physics* 107, 23-39.
- [4] Anderson, J. D. (1989). *Hypersonic and High Temperature Gas Dynamics*. *McGraw-Hill Inc*.
- [5] Yadav, S. (2012). Numerical Simulation and Designanalysis of Simple Shock Tube For Hypersonic Applications. *Department of Mecanical. Engineering, Indian Institute of Technology Guwahati, Assam (India)*.
- [6] Jacobs, P. A. (1998). Shock Tube Modeling with L1d. *Department of Mechanical Engineering, The University of Queensland Reserch Report, 13/98*.

## Author Profile



**Shyam Singh kanwar**, He has done M.Tech. from Indian Institute of Technology; Guwahati, India, in the year 2013. Now he works as an Assistant Professor in the Department of Mechanical Engineering, IT GGU University (A Central University), Bilaspur. His research interest is in the field of CFD and its application, Heat Transfer.

**Gaurav Dubey**, Working as an Assistant Professor in the Department of Industrial & production Engg., Institute of Technology, GGU University, Bilaspur. His area of interest is Solid Mechanics.

**Gouri Shankar Khanday**, Working as an Assistant Professor in the Department of Mechanical Engineering, Institute of Technology, GGU University, Bilaspur. His area of interest is Machine deign.