# Evaluation of Radon Concentration in Indoor Air and Groundwater in Shahjahanpur, Uttar Pradesh, India

Anil Kumar<sup>1</sup>, Prachi<sup>2</sup>, R B S Rawat<sup>3</sup>, V K Sharma<sup>4</sup>

<sup>1</sup>Department of Physics, S. S. (PG) College, Shahjahanpur, Uttar Pradesh, India

<sup>2, 4</sup>Department of Physics, K. G.K. College, Moradabad, Uttar Pradesh, India

<sup>3</sup>Department of Physics, M S (P.G.) College, Saharanpur, Uttar Pradesh, India

Abstract: Radon is a product of the natural radioactive decay of uranium, which occurs naturally in the earth's crust, to radium and then to radon. As radium decays, radon is formed and is released into small air or water-containing pores between soil and rock particles. If this occurs near the soil surface, the radon may be released to ambient air. Radon may also be released into groundwater. If this groundwater reaches the surface, most of the radon gas will quickly be released to ambient air, but small amounts may remain in the water. Evaluation of radon concentration in ground water in Shahjahanpur city of Uttar Pradesh has been carried out using Lucas scintillation cell. Radon concentration was also evaluated in indoor air using solid state nuclear track detector (SSNTD) based twin cup dosimeter technique. Radon concentration was found vary from 9 Bq/m<sup>3</sup> to 78 with an overall average of 31 Bq/m<sup>3</sup>. Radon concentration varies in summer season from 9 Bq/m<sup>3</sup> to 34 Bq/m<sup>3</sup> with an average of 19 Bq/m<sup>3</sup>, during rainy season radon concentration varies from 15 Bq/m<sup>3</sup> to 48 Bq/m<sup>3</sup> with an average of 29 Bq/m<sup>3</sup>, during winter season radon concentration varies from 27 Bq/m<sup>3</sup> to 78 Bq/m<sup>3</sup> with an average of 26 Bq/m<sup>3</sup>. Radon concentration in ground water varies from 3 Bq/l to 25 Bq/l with an overall average of 12 Bq/l.

Keywords: Radon, groundwater, Lucas cell, Indoor air

## 1. Introduction

Radon is a colorless, odorless gas and radioactive by product of radium. It has half life of 3.825 days. It is like carbon-14 gas, is completely natural. Over the course of several days, a radon atom becomes a lead atom. It is produced as a result of  $\alpha$ -decay of radium. It is the most harmful gas present in atmosphere. It is present in atmosphere, environment, soil, ground, water, oil and gas deposits, indoor and outdoor. Since it has half life of 3.8 days and therefore has a much better chance of escaping from material in which it was formed. Hence it reaches the indoor environment as a soil gas from the ground and also from walls, ceilings etc. and other building materials used in construction of human dwellings. In some countries, the radiation dose to man caused by inhaled radon daughters constitutes more than 50% of the total dose (UNSCEAR; 2000, Lubin; 1993). The groundwater radon concentration is expected to reflect not only in chemical form but also in structural properties of rock in an aquifer (Y Sasaki; 1995). The second most important contributor to outer radon is emanation from ground water sources. Ground water in contact with rustle rock penetrates into the pores and voids present in the rocks and soils and dissolves radon that emanates into these spaces following <sup>226</sup>Ra decay. Radon is very soluble in water (Misdaq etal.2000)

In most cases, the movement of radon in water is governed by water transport rather than diffusion. Various investigation is have been made to correlate <sup>222</sup>Rn concentration in water supplies with indoor radon levels in typical homes (Lamresh, J.R., 1983).

## 2. Experimental Methods

The measurements of radon in indoor air and ground water have been carried out by using environmental radiation dosimeter and Lucas scintillation cell respectively. Brief descriptions of these techniques are as follows:

#### Radon measurement in indoor air

Concentration of radon and thoron were measured by using LR-115 Type II plastic track detector. Three small pieces of detector films of size 2.5 cm x 2.5cm were fixed in a twin chamber radon/thoron dosimeter having three different modes. The bare mode gives the values of radon, thoron and their progeny concentrations while the filter and membrane modes records the values due to radon, thoron and pure radon gas, respectively. The dosimeters were suspended inside the house at a height of about two meters from the ground floor. After an exposure time of three months, the detector films were removed etched with 10 % NaOH solution for one hour at a bath temperature of 60°C. The bulk etching rate is about 4 µm/h. The detector films are then washed in distilled water. After washing, the detectors are air dried in dust free environment The detectors, having a residual thickness of 8 µm after etching, are peeled off from their plastic bases and the tracks are registered with spark counter. The recorded track density was then converted in the Bq/m<sup>3</sup> by using an appropriate calibration factor (Ramola et. al., 1996). This measurement was repeated on a time integrated four quarterly cycles to cover all the four seasons of a calendar year.



Figure 1: Schematic diagram of dosimeter

### Radon measurement in groundwater

For the measurements of radon in ground water, a radon tight reagent bottle of one liter capacity holds 750 ml water was taken. The water samples from the ground water were collected. The sample bottle was connected in a closed circuit with Lucas Cell, hand operated rubber pump through a bubbler. The air was circulated in a closed circuit for a period of 15 min until the radon forms a uniform mixture with the air. After sampling the Lucas cell connected to detector and resulting counts were recorded. The observed counts then converted to Bq/l by using the appropriate calibration factor.



Figure 2: Emanometer and dectector with lucas cell

## 3. Results and Discussion

The measured values of radon concentrations in indoor air and groundwater in different seasons are shown in Table 1 & Table 2 respectively.

Location	Summer			Rainy			Winter			Autumn		
	Min	Max	Mean	Min	Max	Mean	Min	Max	Mean	Min	Max	Mean
Ajeej Ganj	12	27	20	22	37	28	43	67	56	16	30	25
Nevada indepur	19	31	26	15	39	27	32	48	39	24	38	31
Lodhipur	11	24	18	17	27	22	27	75	54	27	48	35
Bahadur Ganj	13	34	22	25	42	34	32	47	40	25	30	27
Babujai	9	28	17	25	37	32	33	45	38	21	29	25
Khalil Sarqi	9	17	13	26	48	38	36	68	52	26	39	34
Keruganj	16	33	24	20	34	26	29	47	37	25	37	32
Jalal Nagar	14	28	21	28	36	31	29	47	38	24	34	29
Kachcha Katra	11	23	16	16	34	27	35	62	48.4	17	29	23.6
Hathaura	16	26	21	22	34	28	50	78	62	25	38	32
Anandpuram Colony	10	15	12	19	32	26	40	49	45	26	30	28

**Table 1:** Radon concentration  $(Bq/m^3)$  in indoor air.

Location	Summer			Rainy			Winter			Autumn		
	Min	Max	Mean	Min	Max	Mean	Min	Max	Mean	Min	Max	Mean
Ajeej Ganj	9	19	15	13	22	17	7	14	11	7	18	13
Nevada indepur	8	14	10	4	25	18	9	13	11	9	14	11
Lodhipur	10	17	12	13	19	17	9	16	12	4	12	10
Bahadur Ganj	7	11	9	9	17	12	5	13	9	8	12	10
Babujai	5	12	10	9	16	12	7	12	10	3	12	8
Khalil Sarqi	9	19	14	14	17	15	10	13	12	7	12	10
Keruganj	9	20	14	16	21	19	11	13	12	6	15	11
Jalal Nagar	9	14	10	8	13	11	8	11	10	7	15	11
Kachcha Katra	8	12	11	13	18	15	5	11	9	9	15	11
Hathaura	9	14	11	10	24	16	7	13	10	8	11	9
Anandpuram Colony	12	18	15	11	17	14	3	16	10	4	14	10

Table 2: Radon concentration (Bq/l) in groundwater

International Journal of Science and Research (IJSR) ISSN (Online): 2319-7064 Index Copernicus Value (2013): 6.14 | Impact Factor (2014): 5.611



Figure 3: Seasonal variation of radon concentration in indoor air.



Figure 3: Seasonal variation of radon concentration in groundwater.

The radon concentration in indoor air was found to vary from 9 Bq/m<sup>3</sup> to 78 Bq/m<sup>3</sup>, with an overall average of 31 Bq/m<sup>3</sup>, while in groundwater it was found to vary from 3 Bq/l to 25 Bq/l with an average of 12 Bq/l. Radon concentration in indoor air varies in summer season from 9 Bq/m<sup>3</sup> to 34 Bq/m<sup>3</sup> with an average of 19 Bq/m<sup>3</sup>, during rainy season radon concentration varies from 15 Bq/m<sup>3</sup> to 48 Bq/m<sup>3</sup> with an average of 29 Bq/m<sup>3</sup>, during winter season radon concentration varies from 27 Bq/m<sup>3</sup> to 78 Bq/m<sup>3</sup> with an average of 46 Bq/m<sup>3</sup> and during autumn it varies from 16 Bq/m<sup>3</sup> to 48 Bq/m<sup>3</sup> with an average of 29 Bq/m<sup>3</sup>.

Radon concentration in ground water varies from 3 Bq/l to 25 Bq/l with an overall average of 12 Bq/l. In summer season the radon concentration in groundwater varies from 5 Bq/l to 20 Bq/l with an average of 12 Bq/l, In rainy season radon concentration in groundwater from 4 Bq/l to 25 Bq/l with an average of 15 Bq/l, In winter season radon

concentration in groundwater from 3 Bq/l to 16 Bq/l with an average of 11 Bq/l, In autumn season radon concentration in groundwater 3 Bq/l to 18 Bq/l with an average of 10 Bq/l.

The concentration of radon in indoor air was found least in summer while highest in winter. This is because, in summer season, the houses remain open for long time which contributes in increasing air exchange rate while in winter; the rooms are remaining closed for long hours decreasing air exchange. In groundwater the radon concentration found least in autumn while highest in rainy.

## 4. Conclusions

Based on the results obtained from the study area, the concentrations of radon vary with the season. The concentrations of radon were measured highest in winter and lowest in summer. Indoor radon concentrations in the study area were found to depend on the building materials, mode of construction of a house, ventilation condition of house, volume of the room and geology of the area concentration. The annual overall average levels of radon in the study area were found well below the action levels set by some different countries and institutions. The observed values of radon concentrations in groundwater for different seasons are comparably lower than internationally recommended safe values 4 to 40 Bq/l (UNSCEAR, 1982).

## References

- [1] UNSCEAR, Report to the General Assembly United Nations, New York, 1982.
- [2] Misdaq M.A.;Merzouki A.; Elabboubi D.; Aitnouh F.; Berrazzouk S.,(2000) Determination of radon equivalent alpha doses in different human organs from water ingestion using SSNTD and Dosi. Compartmental Models. J. Radio analytical and Nuclear Chemistry, 245 (3), 513-520.
- [3] Ramola, R.C., Rawat, R.B.S., Kandari, M.S., Ramachandran, T.V., Eappen, K.P. and Subba Ramu, M.C. (1996) Calibration of LR-115 Plastic track detector for environmental radon measurements. Indoor Built Environ. 5, 364-366.
- [4] UNSCEAR, Ionizing Radiation Sources and Biological Effects (New York : United Nations) (1982).
- [5] UNSCEAR, Sources and Effects of Ionizing Radiation (New York : United Nations) (2000)
- [6] J H Lubin and (Jr.) J D Boice J. Nat. Can. Inst. 89 49 (1993).
- [7] G Igarashi, S Saeki, N Takahata, K Sumikawa, S Tasaka, Y Sasaki, M Takahashi and Y Sano Science 269 60 (1995).
- [8] Lamresh J.R., (1993), Introduction to nuclear Engineering, Addison- Wesley Publishing Company.