

occurs at the rate of 1Kbps - 10Kbps. The transmitted data is received by an RF receiver operating at the same frequency as that of the transmitter.

C. Wireless Camera

Here system will continuously capture video frames using wire-less camera.

- 1) Wireless car rearview camera kit
- 2) TV System: NTSC
- 3) Image sensor: color CMOS
- 4) Included Rearview camera, wireless transmitter, wireless receiver
- 5) Adds car rearview function for your car GPS
- 6) 300000 Pixels camera, picture is stable and clear
- 7) Water-proof and dust-proof design
- 8) Camera with max wide angle 170 degree view
- 9) Night vision effective view range: 5 meter
- 10) 2.4GHz wireless transmission technology
- 11) Real-time rear view while back up- suitable for vehicle, trucks, bus and trailer
- 12) Prevents accidents while driving in reverse or parking.

D. Machine Gun

Another main unit in the system is remote controlled and auto triggered machine gun. It is situated on the basement. User can send signal to operate the gun remotely using remote input device MACHINE GUN ROTATION: The rotation of Gun is done by two motors. One in horizontal direction and other in vertical direction, so that user can target or see at any direction by rotating gun using remote input device.

E. Infrared Laser Light

For accurate target at the aim user can use this LASER. It is light emitting diode which generate long distance red laser beam. It is attached with machine gun so that it will move at machine guns direction.

F. Joystick/Keypad

Joystick switches or joysticks are manually actuated control devices for installation in control and front panels as well as in portable control equipment. They are used wherever motion sequences analogous to the actuation direction are controlled by hand. They are ideal for rising, lowering and triggering move-ments to the right and left, just to name same few possibilities. EUCHNER joysticks are used for radio and cable controls, building machinery and cranes. Joysticks as control equipment in remote control devices Remote cable control for concrete pumps.

G. Global System for Mobile

The Global Service for Mobile (GSM) is used for transmit and receive the msg.

5. Applications

Proposed system can be used in various fields like military, spying, tracking etc.

- 1) In military it can be used for land soldier automation.
- 2) Using same technology we can develop different mini robots. These robots can be used for pipe line inspection

for wiring checking and device faults detections.

- 3) Same robots can be sending to detect different environmental statistics in remote area or in space.

6. Conclusion

Self -Defensive Machine Gun system is mainly design to provide remote accessibility using wireless technology for land soldiers in battle field. With the sensors technology it will provide environ-mental statistics and also give full power of atomization system. In future with more development and enhancement it will be ready to work in real world environment.

References

- [1] Do Hyun Kim¹, Ki Sang Hwang¹, Jeong Joo Kwon¹, Sung-Soo Kim², Sung Ho Park³, Stabilization Control for the Mobile Surveillance Robot using Motion Simulator International Conference on Control, Automation and Systems Oct. 14-17, 2008 in COEX, Seoul, Korea.
- [2] Ki Sang Hwang Kyu Jin Park Do Hyun Kim Sung- Soo Kim ,Sung Ho Park Development of a Mobile Surveillance Robot International Conference on Control, Automation and Systems Oct. 17-20, 2007 in COEX, Seoul, Korea.
- [3] Frank S. Cheng A METHODOLOGY FOR DEVELOPING ROBOTIC WORKCELL SIMULATION MODELS2000 Winter Simulation Conference.
- [4] Guoliang Liu',Wanjun Haot, Shizuo Yant,Zengqi Sun2, Wenyi Qiangt A Fusion Algorithm for Building Maps in Confined Environments for Mobile Robots IMACS Multiconference on "Computational Engineering in Systems Applications"(CESA), October 4-6, 2006, Beijing, China.
- [5] Dong Ziwei Tang Liwei Research on Amendment of a Machine Guns Dynamic Characteristics The Eighth International Conference on Electronic Measurement and Instruments ICEMI2007(Weapon Test Center, Shijiazhuang Mechanical Engineering College, Shijiazhuang, Hebei, 050003, China)
- [6] Junji Hirai, Member, IEEE, Tae-Woong Kim, Member, IEEE, and Atsuo Kawa-mura, Senior Member, IEEE Wireless Transmission of Power and Information and Information for Cableless Linear Motor Drive IEEE TRANSACTIONS ON POWER ELECTRONICS, VOL. 15, NO. 1, JANUARY 2000
- [7] Yoshihiko Takahashi* 1, Go Manabe* 1, Katsumi Takahashi*2, and Takuro Hatakeyama*3 Simple Self-Transfer Aid Robotic System Inlerooationnl Con-ference on Robotics and Aufomation Taipei, Taiwan, September 14-19, 2003
- [8] Yongjin Kwon¹, Bill Tseng² and Richard Chiou³ Web-enabled Calibration of Micro Robotic System1Division of Industrial and Information Systems Engineering, Ajou University, Suwon, South Korea(2007)
- [9] Alka R Kaushik, Branko G celler CHARACTERIZATION OF PASSIVE INFRARED SENSORS FOR MONITORING OCCUPANCY PATTERN Pro-ceedings of the 28th IEEE EMBS Annual International Conference New York City, USA, Aug 30- Sept 3, 2006

- [10] C.D. Young, R.J. Leu, C.C. Hung, S.F. Chen, and K.W. Huang Critical Dimension Management of Photo Resister by Lens Heating Compensation and Statistical Process Control Taiwan Semiconductor Manufacturing Company (TSMC) No. 121, Park Ave. 3, Science-Based Industrial Park, Hsin-Chu, Taiwan, R.O.C.,2000
- [11] Shusun Li, Xiaobing Zhou, and Kim Morris Measurement of Snow and Sea Ice Surface Temperature and Emissivity in the Ross Sea Geophysical Institute, University of Alaska Fairbanks, Fairbanks, AK 99775 903 Koyukuk Drive, P.O. Box 757320, Fairbanks, AK 99775-7320, USA,1999
- [12] Morrie son G.D. A camera based input device for large interactive displays Computer Graphics and Applications, IEEE July-Aug. 2005
- [13] N. Nikolaidis and I. Pitas, Copyright protection of images using robust digital signatures, in Proc. IEEE ICASSP96, 1996, pp. 21682171.
- [14] M. D. Swanson, B. Zhu, and A. H. Tewfik, Robust data hiding for images, in Proc. IEEE Digital Signal Processing Workshop, Loen, Norway, Sept. 1996, pp. 3740.

