

Various protocol was developed and security issue was also be added with the protocol. Various cryptographic techniques will be developed which provides security to the communication between the tag and the reader and avoid the possibility of eavesdropping and clandestine tracking. Thus design of the tag typical RFID system in FPGA improves various parameters of the overall system like performance, power optimization and security.

References

- [1] Alex K. Jones, Raymond R. Hoare, Swapna R. Dontharaju, Shenchih Tung, Ralph Sprang, Josh Fazekas, James T. Cain, and Marlin H. Mickle, "An Automated, Reconfigurable, Low-Power RFID Tag", DAC 2006, July 24-28, 2006, pp 131-136.
- [2] Jianping Wang Huiyun Li and Fengqi Yu, "Design of Secure and Low-cost RFID Tag Baseband", 1-4244-1312-5/07 © 2007 IEEE, pp. 2066-2069.
- [3] Su-Bong Ryu, Jin-Oh Jeon, and Min-Sup Kang, "FPGA Design of Digital Codec for Passive RFID Tag", 2007 IEEE DOI 10.1109/ALPIT.2007.99, pp. 343-346.
- [4] Yujing Feng, Wei Zhang, Xiaohui Xing, "Digital part in 915MHz UHF RFID tag", 978-1-4244-4076-4/09/ ©2009 IEEE, pp. 115-119
- [5] Jiaxin Wang and Dongkai Yang, "Design of a Multi-protocol RFID Tag Simulation Platform Based on Supply Chain", 978-1-4244-4639-1/09 ©2009 IEEE,
- [6] Erich Wenger, Thomas Baier, and Johannes Feichtner' "JAAVR: Introducing the Next Generation of Security-enabled RFID Tags", 2012 15th Euromicro Conference on Digital System Design, 978-0-7695-4798-5/12©2012 IEEE DOI 10.1109/DSD.2012.81, pp. 640-645.
- [7] Omar Abdelmalek, David Hely and Vincent Beroule, "EPC Class 1 GEN 2 UHF RFID tag emulator for robustness evaluation and improvement", 2013 8th International Conference on Design & Technology of Integrated Systems in Nanoscale Era (DTIS), pp. 20-24
- [8] Anuj, Ramandeep Kaur, "Baseband Processor of Multi-Purpose RFID Tag using VHDL", International Journal of Science and Research (IJSR), Volume 3 Issue 3, March 2014, Paper ID: 020131084.