# A Review of Physical Layer of Mobile WiMAX System and OFDM

# Deepti Rai<sup>1</sup>, Roshni Jaiswal<sup>2</sup>

<sup>1</sup>Professor of Electronics and Comm. Engg. Dept., Alpine Institute of Technology, Ujjain (M.P.)

<sup>2</sup>Student of Electronics and Comm. Engg. Dept., Alpine Institute of Technology, Ujjain (M.P.)

Abstract: The WiMAX technology based on the IEEE 802.16-2004 Air Interface Standard israpidly proving itself as a technology that will play a key role in fixed broadband wirelessmetropolitan area networks. The first certification lab, established at Cetecom Labs inMalaga, Spain is fully operational and more than 150 WiMAX trials are underway inEurope, Asia, Africa and North and South America. Unquestionably, Fixed WiMAX,based on the IEEE 802.16-2004 [1] Air Interface Standard, has proven to be a cost-effective fixed wireless alternative to cable and DSL services. In December, 2005 theIEEE ratified the 802.16e amendment [2] to the 802.16 standard. This amendment addsthe features and attributes to the standard necessary to support mobility. The WiMAXForum is now defining system performance and certification profiles based on the IEEE802.16e Mobile Amendment and, going beyond the air interface, the WiMAX Forum isdefining the network architecture necessary for implementing an end-to-end MobileWiMAX2 network. Release-1 system profiles will be completed in early 2006. This particular paper focuesses on giving an overview of the mobile Wimax technology and LDPC coding typically used to enhance the performance of OFDM systems.

Keywords: OFDM, WiMAX, Physical Layer, QoS, Circular prefix

#### 1. Introduction to Mobile WiMAX

Mobile WiMAX is a broadband wireless solution that enables convergence of mobile and fixed broadband networks through a common wide area broadband radio accesstechnology and flexible network architecture. The Mobile WiMAX Air Interface adoptsOrthogonal Frequency Division Multiple Access (OFDMA) for improved multipathperformance in non-line-of-sight environments. Scalable OFDMA (SOFDMA) [3] is introduced in the IEEE 802.16e Amendment to support scalable channel bandwidths from 1.25 to 20 MHz. The Mobile Technical Group (MTG) in the WiMAX Forum isdeveloping the Mobile WiMAX system profiles that will define the mandatory and optional features of the IEEE standard that are necessary to build a Mobile WiMAX-compliant air interface that can be certified by the WiMAX Forum. The Mobile WiMAXSystem Profile enables mobile systems to be configured based on a common base featureset thus ensuring baseline functionality for terminals and base stations that are fully interoperable.

Some elements of the base station profiles are specified as optional toprovide additional flexibility for deployment based on specific deployment scenarios thatmay require different configurations that are either capacity-optimized or coverage-optimized. Release-1 Mobile WiMAX profiles will cover 5, 7, 8.75, and 10 MHz channelbandwidths for licensed worldwide spectrum allocations in the 2.3 GHz, 2.5 GHz, 3.3GHz and 3.5 GHz frequency bands. The WiMAX Forum Network Working Group (NWG) is developing the higher-levelnetworking specifications [4] for Mobile WiMAX systems beyond what is defined in theIEEE 802.16 standard that simply addresses the air interface specifications. The ombined effort of IEEE 802.16 and the WiMAX Forum help define the end-to-endsystem solution for a Mobile WiMAX network.Mobile WiMAX systems offer scalability in both radio access technology and networkarchitecture, thus providing a great deal of flexibility in network deployment options and service offerings.



Figure 1: Mobile WiMAX system Profile

### 2. Salient Features Supported by Mobile WiMAX

Some of the salient features supported by Mobile WiMAX are:

• **High Data Rates:** The inclusion of MIMO antenna techniques along with flexiblesub-channelization

schemes, Advanced Coding and Modulation all enable theMobile WiMAX technology to support peak DL data rates up to 63 Mbps per sectorand peak UL data rates up to 28 Mbps per sector in a 10 MHz channel.

• Quality of Service (QoS): The fundamental premise of the IEEE 802.16 MACarchitecture is QoS. It defines Service Flows which can map to DiffServ code pointsor

# Volume 6 Issue 12, December 2017 www.ijsr.net

Licensed Under Creative Commons Attribution CC BY

MPLS flow labels that enable end-to-end IP based QoS. Additionally, sub-channelization and MAP-based signaling schemes provide a flexible mechanism foroptimal scheduling of space, frequency and time resources over the air interface on aframe-by-frame basis.

- Scalability: Despite an increasingly globalized economy, spectrum resources forwireless broadband worldwide are still quite disparate in its allocations. MobileWiMAX technology therefore, is designed to be able to scale to work in differentchannelizations from 1.25 to 20 MHz to comply with varied worldwide requirementsas efforts proceed to achieve spectrum harmonization in the longer term. This alsoallows diverse economies to realize the multi-faceted benefits of the Mobile WiMAXtechnology for their specific geographic needs such as providing affordable internetaccess in rural settings versus enhancing the capacity of mobile broadband access inmetro and suburban areas.
- Security: The features provided for Mobile WiMAX security aspects are best inclass with EAP-based authentication, AES-CCM-based authenticated encryption, and CMAC and HMAC based control message protection schemes. Support for adiverse set of user credentials exists including; SIM/USIM cards, Smart Cards, Digital Certificates, and Username/Password schemes based on the relevant EAPmethods for the credential type.
- Mobility: Mobile WiMAX supports optimized handover schemes with latencies lessthan 50 milliseconds to ensure real-time applications such as VoIP perform withoutservice degradation. Flexible key management schemes assure that security ismaintained during handover.While the Mobile WiMAX standards activity has been progressing, equipment suppliershave been aggressively developing equipment that will be WiMAX/802.16e-2005compliant. With commercial Mobile availability of WiMAX-compliant equipmentanticipated in the very near future and the

launch of WiBro services this year in Korea, itbegs the question as to how the Mobile WiMAX technology relates to and impacts concurrent advances in 3G cellular technology. To address this question it is necessary togain an understanding of the underlying technology for Mobile WiMAX as well as theplanned 3G enhancements.

# 3. OFDMA basics for mobile WiMAX

Orthogonal Frequency Division Multiplexing (OFDM) [6,7] is a multiplexing techniquethat subdivides the bandwidth into multiple frequency sub-carriers as shown in Figure 2.In an OFDM system, the input data stream is divided into several parallel sub-streams of reduced data rate (thus increased symbol duration) and each sub-stream is modulated andtransmitted on a separate orthogonal subcarrier. The increased symbol duration improves he robustness of OFDM to delay spread. Furthermore, the introduction of the cyclicprefix (CP) can completely eliminate Inter-Symbol Interference (ISI) as long as the CPduration is longer than the channel delay spread. The CP is typically a repetition of thelast samples of data portion of the block that is appended to the beginning of the datapayload as shown in Figure 3. The CP prevents interblock interference and makes the channel appear circular and permits low-complexity frequency domain equalization.

A perceived drawback of CP is that it introduces overhead, which effectively reducesbandwidth efficiency. While the CP does reduce bandwidth efficiency somewhat, theimpact of the CP is similar to the "roll-off factor" in raised-cosine filtered single-carriersystems. Since OFDM has a very sharp, almost "brick-wall" spectrum, a large fraction of the allocated channel bandwidth can be utilized for data transmission, which helps tomoderate the loss in efficiency due to the cyclic prefix.



Figure 2: Basic Architecture of an OFDM System

OFDM exploits the frequency diversity of the multipath channel by coding and interleaving the information across the sub-carriers prior to transmissions. OFDM modulation can be realized with efficient Inverse Fast Fourier Transform (IFFT), which enables a large number of sub-carriers (up to 2048) with low complexity. In an OFDMsystem, resources are available in the time domain by means of OFDM symbols and in the frequency domain by means of subcarriers. The time and frequency resources can be organized into sub-channels for allocation to individual users.

#### Volume 6 Issue 12, December 2017 www.ijsr.net

Licensed Under Creative Commons Attribution CC BY

Orthogonal FrequencyDivision Multiple Access (OFDMA) is a multiple-access/multiplexing scheme thatprovides multiplexing operation of data streams from multiple users onto the downlinksub-channels and uplink multiple access by means of uplink sub-channels.



Figure 3: Insertion of Cyclic Prefix

# 4. OFDMA Symbol Structure and Sub Chanellization

The OFDMA symbol structure consists of three types of sub-carriers as shown in Figure 4:

- Data sub-carriers for data transmission
- Pilot sub-carriers for estimation and synchronization purposes
- Null sub-carriers for no transmission; used for guard bands and DC carriers



Figure 4: OFDMA Sub-Carrier Structure

Active (data and pilot) sub-carriers are grouped into subsets of sub-carriers called sub-channels. The WiMAX OFDMA PHY [3] supports sub-channelization in both DL and UL. The minimum frequency-time resource unit of subchannelization is one slot, which is equal to 48 data tones (sub-carriers).There are two types of sub-carrier permutations sub-channelization; diversity for and contiguous. The diversity permutation draws sub-carriers pseudo-randomly to form asub-channel. It provides frequency diversity and inter-cell interference averaging. Thediversity permutations include DL FUSC (Fully Used Sub-Carrier), DL PUSC (PartiallyUsed Sub-Carrier) and UL PUSC and additional optional permutations. With DL PUSC, for each pair of OFDM symbols, the available or usable sub-carriers are grouped intoclusters containing 14 contiguous sub-carriers per symbol period, with pilot and dataallocations in each cluster in the even and odd symbols as shown in Figure 5.



A re-arranging scheme is used to form groups of clusters such that each group is made upof clusters that are distributed throughout the sub-carrier space. A sub-channel in a group contains two (2) clusters and is made up of 48 data sub-carriers and eight (8) pilot sub-carriers. The data subcarriers in each group are further permutated to generate sub-channels within the group. Therefore, only the pilot positions in the cluster are shown in Figure 5. The data subcarriers in the cluster are distributed to multiple subchannels. Analogous to the cluster structure for DL, a tile structure is defined for the UL PUSC whose format is shown in Figure 6



# Volume 6 Issue 12, December 2017

<u>www.ijsr.net</u> Licensed Under Creative Commons Attribution CC BY

Paper ID: ART20178107

DOI: 10.21275/ART20178107

The available sub-carrier space is split into tiles and six (6) tiles, chosen from across theentire spectrum by means of a re-arranging/permutation scheme, are grouped together toform a slot. The slot comprises 48 data sub-carriers and 24 pilot sub-carriers in 3 OFDMsymbols.The contiguous permutation groups a block of contiguous sub-carriers to form a sub-channel. The contiguous permutations include DL AMC and UL AMC, and have thesame structure. A bin consists of 9 contiguous sub-carriers in a symbol, with 8 assigned for data and one assigned for a pilot. A slot in AMC is defined as a collection of bins of the type (N x M = 6), where N is the number of contiguous bins and M is the number of contiguous symbols. Thus the allowed combinations are [(6 bins, 1 symbol), (3 bins, 2symbols), (2 bins, 3 symbols), (1 bin, 6 symbols)]. AMC permutation enables multi-userdiversity by choosing the sub-channel with the best frequency response.In general, diversity subcarrier permutations perform well in mobile applications whilecontiguous sub-carrier permutations are well suited for fixed, portable, or low mobilityenvironments. These options

enable the system designer to trade-off mobility forthroughput.

# 5. Other Advanced Phy Layer Features

Adaptive modulation and coding (AMC), Hybrid Automatic Repeat Request (HARQ)and Fast Channel Feedback (CQICH) were introduced with Mobile WiMAX to enhancecoverage and capacity for WiMAX in mobile applications.Support for QPSK, 16QAM and 64QAM are mandatory in the DL with Mobile WiMAX.In the UL, 64QAM is optional. Both Convolutional Code (CC) and Convolutional TurboCode (CTC) with variable code rate and repetition coding are supported. Block TurboCode and Low Density Parity Check Code (LDPC) are supported as optional features. Table 1 summarizes the coding and modulation schemes supported in the MobileWiMAX profile the optional UL codes and modulation are shown in italics.

		DL	UL	
Modulation		QPSK, 16QAM, 64QAM	QPSK,16QAM, 64QAM	
Code Rate	CC	1/2, 2/3, 3/4, 5/6	1/2, 2/3, 5/6	
	CTC	1/2, 2/3, 3/4, 5/6	1/2, 2/3, 5/6	
	Repetition	x2, x4, x6	x2, x4, x6	1

 Table 1: Supported Code and Modulations

The frame duration is 5 milliseconds. Each frame has 48 OFDMsymbols, with 44 OFDM symbols available for data transmission. The highlighted values indicate data rates for optional 64QAM in the UL. The base station scheduler determines the appropriate data rate (or burst profile) for eachburst allocation based on the buffer size, channel propagation conditions at the receiver, etc.

A Channel Quality Indicator (CQI) channel is utilized to provide channel-stateinformation from the user terminals to the base station scheduler. Relevant channel-state information can be fed back by the CQICH including: Physical CINR, effective CINR, MIMO mode selection and frequency selective sub-channel selection. With TDD implementations, link adaptation can also take advantage of channel reciprocity toprovide a more accurate measure of the channel condition (such as sounding).Hybrid Auto Repeat Request (HARQ) is supported by Mobile WiMAX. HARQ isenabled using N channel "Stop and Wait" protocol which provides fast response to packeterrors and improves cell edge coverage. Chase Combining and optionally, IncrementalRedundancy are supported to further improve the reliability of the retransmission. Adedicated ACK channel is also provided in the uplink for HARQ ACK/NACK signaling.

Multi-channel HARQ operation is supported. Multi-channel stop-and-wait ARQ with asmall number of channels is an efficient, simple protocol that minimizes the memory required for HARQ and stalling [8]. WiMAX provides signaling to allow fullyasynchronous operation. The asynchronous operation allows variable delay between retransmissions which gives more flexibility to the scheduler at the cost of additional overhead for each retransmission allocation. HARQ combined together with CQICH and AMC provides robust link adaptation in mobileenvironments at vehicular speeds inexcess of 120 km/hr.

# References

- [1] "Air Interface for Fixed Broadband Wireless Access Systems," IEEE STD 802.16 – 2004, October, 2004.
- [2] "Air Interface for Fixed and Mobile Broadband Wireless Access Systems," IEEE P802.16e/D12,February, 2005.
- [3] Hassan Yagoobi, "Scalable OFDMA Physical Layer in IEEE 802.16 WirelessMAN", Intel TechnologyJournal, Vol 08, August 2004.
- [4] "WiMAX End-to-End Network Systems Architecture -Stage 2: Architecture Tenets, Reference odel and Reference Points," WiMAX Forum, December, 2005.
- [5] "Mobile WiMAX Part II: A Comparative Analysis", WiMAX Forum, 2006
- [6] L.J. Cimini, "Analysis and Simulation of a Digital Mobile Channel Using Orthogonal FrequencyDivision Multiplexing," IEEE Trans. Comm., vol. COM-33, no. 7, pp 665-675, June 1985.
- [7] Richard Van Nee and Ramjee Prasad, "OFDM for Wireless Multimedia Communications," Artech House,2000.
- [8] W. Xiao and R. Ratasuk, "Analysis of Hybrid ARQ with Link Adaptation", Proceedings of the AnnualAllerton Conference on Communications, Control, and Computing, pp. 1618-1619, Oct 2002.
- [9] G. Nair, J. Chou, T. Madejski, K. Perycz, P. Putzolu and J. Sydir "IEEE 802.16 Medium Access Controland Service Provisioning", Intel Technology Journal, vol 08, August 2004.

# Volume 6 Issue 12, December 2017 www.ijsr.net

Licensed Under Creative Commons Attribution CC BY

- [10] F. Wang, A. Ghosh, R. Love, K. Stewart et.al., "IEEE 802.16e System Performance-Analysis andSimulation Results", Proc. of PIMRC, Berlin, Germany, Sept. 2005.
- [11] Philippe Duplessis, "HSOPA: Exploiting OFDM and MIMO to take UMTS beyond HSDPA/HSUPA", Nortel Technical Journal, Issue 2, July 2005.
- [12] John Hoadley and Al Javed, "Overview: Technology Innovation for Wireless Broadband Access", NortelTechnical Journal, Issue 2, July 2005.
- [13] John Liva and Titus Kwok-Yeung Lo, "Digital Beamforming in Wireless Communications," ArtechHouse Publishers, 1996.
- [14] S.M. Alamouti, "A Simple Transmit Diversity Technique for Wireless Communications," IEEE Journalon Selected Areas in Communications, vol. 16, pp 1451-1458, October 1998.
- [15] V. Tarokh, H. Jafarkhani and A. R. Calderbank, "Spacetime Block Codes from Orthogonal Designs,"IEEE Transactions on Information Theory, vol. 45, pp. 1456-1467, July 1999.