International Journal of Science and Research (IJSR) ISSN (Online): 2319-7064 Index Copernicus Value (2015): 78.96 | Impact Factor (2015): 6.391

# Estimation Of Hydraulic Conductivity And Transmissivity Of Quarternary Deposit Aquifer Using Vertical Electrical Sounding in Kertajati Majalengka West Java

Andi Agus Nur<sup>1</sup>, Gumilar Utamas Nugraha<sup>2</sup>, Pulung Arya Pranantya<sup>3</sup>

<sup>1</sup>Faculty of Geological Engineering, Padjadjaran University, Bandung, Indonesia Jl. Raya Bandung-Sumedang Km. 21 Jatinangor, West Java, Indonesia

<sup>2</sup>Alumni of Geological Engineering Master Program, Faculty of Geological Engineering, Padjadjaran University, Bandung, Indonesia Jl. Raya Bandung-Sumedang Km. 21 Jatinangor, West Java, Indonesia

<sup>3</sup>Research Center for Water Resources, Research and Development Agency, Ministry of Public Works and Housing, Indonesia. Jl. Ir. H. Djuanda No.193 Bandung, Jawa Barat

Abstract: The integration of geophysical data with direct hydrogeological measurements can provide a minimally invasive approach to characterize the subsurface at a variety of resolutions and over many spatial scales. The field of hydrogeophysics has attracted much attention during the last two decades. In this domain, the geophysical data inverted to geophysical models are interpreted in terms of the hydrogeology to serve as a basis for the definition of hydraulic models in the areas of interest. The hydraulic conductivity (K) value measured in a reference borehole has been combined with the electrical conductivity obtained from nearby Vertical Electrical Sounding data in the Kertajati confined aquifer. The resulting relation was interpreted with Dar Zarrouk parameters to infer the transmissivity variations at other vertical electrical sounding locations, where (K) values are unknown. The results indicate that the transmissivity values in the aquifer of interest vary from 553.935 to 14074  $m^2/day$ , and K varies from 38.48 to 203.776 m/day throughout the studied area.

Keywords: Geophysics, Hydraulic Conductivity, Transmissivity, Vertical Electrical Sounding

#### 1. Introduction

Groundwater and aquifers are characterized by a number of parameters which can be determined by surface geophysical measurements; commonly porosity, transmissivity and conductivity. The occurrence and movement of groundwater depends on subsurface characteristics, such as lithology, texture and structure. Hydraulic conductivity/ permeability (K), Transmissivity (T), and Storativity (S) are all commonly applied hydraulic parameters in the modelling of groundwater flow [5]. Hydraulic conductivity (K) and transmissivity (T) are important parameters for assessment of aquifers. They describe the general ability of an aquifer to transmit water over a unit thickness for hydraulic conductivity and over the entire saturated thickness for transmissivity. The conventional method for determining aquifer parameters is a pumping test, which is expensive and yields results appropriate only to a small region of the aquifer. These methods are expensive and time consuming especially when a large set of data is required Because the hydraulic parameters of geologic formations vary over relatively small spatial scales, it is difficult to accurately characterize subsurface aquifer properties using just the information obtained from widely spaced boreholes. A more complete and accurate characterization of the subsurface can be achieved by using an integrated exploration approach in which borehole and geophysical data are jointly interpreted [1]. Surface geophysical methods have been developed as an alternative to field hydrogeological methods. These provide rapid and effective techniques for groundwater exploration and aquifer evaluation [16].

The investigation of the spatial distribution of aquifer properties from geophysical measurements has received great interest over the past two decades [1] [16]. A key step in quantitative hydrogeophysical interpretations is the transformation of the measured geophysical properties into the desired hydrogeological parameters.

Although various geophysical techniques are currently being applied to explore and assess water resources, the directcurrent (DC) electrical resistivity method still proves the most powerful and cost-effective technique in groundwater studies [9] [11]. This is due to the closerelationship between the electrical conductivity and some hydrogeological properties of the aquifer. Moreover, subsurface lithological information and the depth to water obtained from the existing boreholes were used to confirm the results of the measured data inversion. Accordingly, this report shows how the geoelectrical parameters can be used for the estimation of transmissivity and hydraulic conductivity variations throughout kertajati research area.

#### 2. Regional Geology

Geology of the study area included in the Geological Map of Arjawinangun Quadrangle. It is composed of Lower Quaternary Sedimentary Rocks (Qos) and Aluvium Deposition (Qa). Lower Quaternary Sedimentary Rocks

Volume 6 Issue 9, September 2017 <u>www.ijsr.net</u> Licensed Under Creative Commons Attribution CC BY (Qos) large extend almost throughout the study site and consist of tuffaceous sandstones, sand, silt tuffaceous clays, conglomerates and breccias and tuffaceous contains pumice, as revealed in the Kertajati Village form of conglomerates and Pasiripis Village form of coarse sand. This form of soil weathering residue (residual soils) in the form of yellowish brown clay plastic and swelling.



Figure 1: Geological map of the study area (modified from Djuri 1995)

Alluvium (Qa) Holocene age are in the southeastern part of the study area, the flood plains of the River Cimanuk deposition results. Alluvium deposits consist of clay, silt and sand (Hasibuan, 2009). According to Hasibuan (2009), rocks are found in the village of Kertajati and in the village of Pasiripis. In the Kertajati Village rocks form a conglomerate with strong weathered condition, so that the gravel fragments apart, whereas in the Pasiripis Village form of layered sandstone medium sized grains with a fragile condition. The residual soil is the result of weathering of Quaternary sedimentary rock (Qos) consisting of: sand, silt, and clay. The soil is transported which is an alluvium deposit.

#### Geomorphology



Figure 2: Slope map of the study area

The location of the study was a wavy plateau with an altitude of 25 - 37.5 m above sea level (dpl), with a slope of less than 3% to the southeast (Figure 2). The rivers in the study area are seasonal rivers that can be separated into rivers flowing north and south and east to Cimanuk River. Study area are included in the Cimanuk River Basin, Kalicilet, Cibuaya, and

PasiranginWhere each basin has an area of 3739 km<sup>2</sup>, 415 km<sup>2</sup>, 471 km<sup>2</sup>, 66 km<sup>2</sup>. In areas of depression, there are swamps that function as retention used in the dry season. The swamps include Rawa Cicabe and Rawa Telik in Pasiripis Village, Rawa Cimaneuh and Rawa Jawura in Kertajati Village, and several swamps in Sukakerta Village



Figure 3: Watershed map of the study area

#### Hydrogeology

Based on the Report by IWACO-WASECO The Majalengka region shows the dominance of Ciremai volcano in the southeast and has a height up to 3078 m above sea level. The volcano appears on the sediment of Tertiary-aged sea sediments consisting mainly of claystone. The rocks are mainly exposed in the south and west of the district and covered by alluvial / talus deposits in the northern coastal plains. Based on its hydrogeological characteristics, this area can be divided into several zones: Quarter volcanic deposits, Tertiary sediment deposition, Sedimentation of Quaternary Volcano fan, Alluvial deposits, Alluvial river Cimanuk and Cilutung, Cikijing Basin

# 3. Methods

#### Methodology and data acquisition

Electrical methods are widely applied in hydrogeophysical investigations [3]. VES sounding measurements have been conducted in the studied area to identify groundwater occurrences [13][17]. The VES data were measured at 12 points arranged in a grid-like pattern, using a GL-4200 resistivity meter. A Schlumberger electrode array was applied with current electrode spacing (AB/2) ranging from 1.5 to 150 m.

DOI: 10.21275/ART20176267



Figure 4: VES measurement points (red dots), green triangle Borehole

#### **Data inversion**

In the present work, the VES inverted in a one-dimensional (1-D) scheme. The VES data were inverted using Russian software [8], where well information was used for building up the initial models. The geophysical studies conducted in this area revealed the following results; the aquifer exhibits relatively low resistivity values ranging from 13.3 to 133 Ohm-m (Fig. 5a), and thickness values ranging from 9.13 to 69 m as shown in Fig. 5b. This aquifer is composed of Sand deposits.



**Figure 5:** (a) Lateral Distribution of Aquifer Resistivity (b) isopach Aquifer (thickness in meter)

#### Transmissivity-Dar Zarrouk approach

The theory and mathematical expressions used for groundwater investigation by geoelectrical methods are well established [10] [3] [11]. Mathematically, the flow of electrical current in a conducting medium is governed by Ohm's law and groundwater flow in a porous medium is controlled by Darcy's law, where both have similar formulae as follows:

$$J = \sigma E (Ohm's \, law)$$

$$Q = K I A (Ohm's law)$$

where, J = electric current density,  $\sigma =$  electrical conductivity, E = electric field intensity, Q = discharge (volume of water per unit time), K = hydraulic conductivity, I = hydraulic gradient, A = cross-sectional area perpendicular to the direction of flow. The analogy between these two macroscopic phenomena and the relationship between electric and hydraulic parameters are widely accepted [5][4]. Groundwater flow through an aquifer is governed by the bulk parameter, transmissivity (T), which is expressed by:

$$T = K h$$

where, h = saturated thickness of the aquifer. Therefore, it is more appropriate to develop a relation between transmissivity and the Dar Zarrouk parameters. The Dar Zarrouk parameters were first introduced by [12] to explain the problem of non-uniqueness in the interpretation of resistivity depth sounding curves. They consist of two variables which can be assigned to each horizontal layer of a simple stratified model; the transverse resistance *T* and the longitudinal conductan (S).

$$T = hp = h/\sigma \dots$$
 and  $\dots S = h/\sigma$ 

where, h is the saturated thickness of the layer (in meters) and  $\rho$  is the electrical resistivity of the layer in Ohm-meters which is equivalent to 1/conductivity ( $\sigma$ ).

[14] have established an ana-lytical relationship between the aquifer transmissivity (T) and both the transverse resistance (T) and the longitudinal conductance (S). Taking into account a prism of aquifer

$$T = (K\sigma)T$$

and,  $T = (K\sigma)T$ In areas of similar geologic setting and water quality, the K\_ $\sigma$  product (the K to  $\sigma$  relation, either Kmultiplied by or divided by  $\sigma$ ) remains fairly constant[14] [15]. Estimation of the appropriate constant (either K  $\sigma$ orK/ $\sigma$ ) can be done by combining aquifer pumping test results and surface conductivity measurements at a few points in the aquifer. Then, transmissivity variations over the rest of the aquifer can easily be determined from additional conductivity measurements.

#### 4. Result and Discussion

Prior to the investigation of transmissivity variations throughout the aquifer of interest, it was necessary to calculate the appropriate K  $\sigma$  constant. The K\_ $\sigma$  product can

# Volume 6 Issue 9, September 2017 www.ijsr.net

Licensed Under Creative Commons Attribution CC BY

be expressed in terms of both transverse resistance (T) and longitudinal conductance (S). In this case study, T and S values at all stations could be calculated by means of resistivities and thicknesses obtained from the VES data modeling. Regarding the VES method, the transverse resistance is the dominant parameter for a layer with a Kshaped sounding curve while a layer with an H-type curve [6].

# **Table 2** Estimated transmissivity values obtained from the combining of $K/\sigma$ constant with the longitudinal conductances at all stations in the studied area

ID VES	h	ρ	$S = h/\rho$	$T=(K/\sigma)S$	K = (T/h)
MJL 1	23.9	33.9	0.705015	1912.636	80.02662
MJL 2	26.8	133	0.201504	546.6601	20.39776
MJL 3	69	13.3	5.18797	14074.46	203.9776
MJL 4	12.41	29.8	0.416443	1129.769	91.037
MJL 5	13.66	66.9	0.204185	553.9349	40.55161
MJL 6	13.01	57.5	0.226261	613.8237	47.18091
MJL 7	12.6	70.5	0.178723	484.8592	38.48089
MJL 8	9.13	41.2	0.221602	601.1845	65.84715
MJL 9	11.8	26.6	0.443609	1203.468	101.9888
MJL 10	20.6	41.9	0.491647	1333.79	64.74708
MJL 11	14.8	33.1	0.44713	1213.02	81.9608
MJL 12	9.81	32.6	0.30092	816.3673	83.21787

Remarks:  $\rho$  electrical resistivity (Ohm-m); h saturated thickness (m); S longitudinal conductance; K hydraulic conductivity (m/day);  $\sigma$  = electrical conductivity (Siemens/m).

#### T transmissivity $(m^2/day)$

*K*/ $\sigma$  constant: the *K*/ $\sigma$  constant was calculated by using the *K* value obtained from the pumping test (*K* = 15.6 m/day) and  $\sigma$  obtained from  $\rho$  = 48.35 Ohm-m ( $\sigma = \frac{1}{\rho} = \frac{1}{48.35} = 0.0207$  Siemens/m



Figure 7: Lateral Distribution of Hydraulic conductivity in study area

# 5. Conclusion

The present study is an attempt to demonstrate a quick, simple and relatively inexpensive method for estimating the transmissivity variations throughout aquifer. The results gave a useful first approximation for the transmissivity changes, which will be very useful for further studies of the groundwater regime in the study area. This approximation can be used to site exploratory boreholes or as an initial input to a groundwater flow model.

Application of the Dar Zarrouk parameters for transmissivity estimation is an advantageous approach over resistivity or thickness-dependent estimations. This is based on the fact that both the transmissivity and the Dar Zarrouk parameters are bulk parameters, and do not depend on independent geoelectrical parameters. Since the area is highly fractured, determination of the aquifer geoelectrical properties by a single geophysical method may be a very difficult task. So, themiho integrated interpretation of galvanic and inductive data sets has been conducted to overcome the problems of equivalence and layer suppression encountered in a Ksingle method.

# 6. Acknowledgements

Author greatly appreciates Mr. Adang Soewali Sadikin for his support to my research and for discussion. Everyone in Research Center for Water Resources, Research and Development Agency, Ministry of Public Works, Indonesia.

# References

- Allen DJ, Brewerton LJ, Coleby LM, Gibbs BR, Lewis MA, Macdonald AM, Wagstaef SJ, Williams AZ (1997) The physical properties of major aquifers in England and Wales. Technical Report, WD/97/34, British Geological Survey, Keyworth, UK
- [2] Bhattacharya PK, Patra HP (1968) Direct current geoelectric sounding. Elsevier, Amsterdam, pp 4–7
- [3] Fitterman DV, Stewart MT (1986) Transient electromagnetic sounding for groundwater. Geophysics 51:995–1005
- [4] Fitts CR (2002) Groundwater science. Elsevier, Amsterdam, The Netherlands, pp 167–175
- [5] Freeze RA, Cherry JA (1979) Groundwater. Prentice-Hall, Englewood Cliffs, NJ
- [6] Frohlich RK, Kelly WE (1985) The relation between hydraulic transmissivity and transverse resistance in a complicated aquifer of glacial outwash deposits. J Hydrol 79:529–556
- [7] HM, Osman SSh (2006) Characterization of the groundwater aquifers using combined modeling of VES-TEM data in El-Bruk area, central Sinai, Egypt. NRIAG J Geophys 5(1):1–28
- [8] IPI2Win-1D Program (2000) Programs set for 1D VES data interpretation. Dept. of Geophysics, Geological faculty, Moscow University, Moscow
- [9] Jupp DLB, Vozoff K (1975) Joint inversion of geophysical data. Geophys J Roy Astron Soc 42:977– 991
- [10] Keller GV, Frischknecht FC (1966) Electrical methods in geophysical prospecting. Pergamon, New York
- [11] Koefoed O (1979) Geosounding principle-1. Elsevier, Amsterdam, pp 170–181
- [12] Maillet R (1947) The fundamental equations of electrical prospecting. Geophysics 12(4):529–556
- [13] Massoud U (2005) Geophysical studies for groundwater exploration in El-Bruk area, north central Sinai, Egypt. PhD Thesis, Minoufiya Univ., Egypt, 130 pp

# Volume 6 Issue 9, September 2017

<u>www.ijsr.net</u>

Licensed Under Creative Commons Attribution CC BY

- [14] Niwas S, Singhal DC (1981) Estimation of aquifer transmissivity from Dar-Zarrouk parameters in porous media. J Hydrol 50:393-399
- [15] Onuoha KM, Mbazi FCC (1988) Aquifer transmissivity from electrical sounding data: the case of Ajalli sandstone aquifers, south east of Enugu, Nigeria. In: Ofoegbu CO (ed) Groundwater and mineral resources of Nigeria. Vieweg, Braunschweig, Germany, pp 17-29
- [16] Singh KP (2005) Nonlinear estimation of aquifer parameters from surficial resistivity measurements. Hydrol Earth Syst Sci Discuss 2:917-938
- [17] Sultan SA, Khalil MA, Massoud U, Hassaneen AGh, El-Shaveb

### **Author Profile**



Andi Agus Nur he is Lector in Faculty of Geology, Padjadjaran University. He received the B. Sc. Degree from Padjadjaran University, master degree from Bandung Institute of Technology, Indonesia and Doctor degree from Padjadjaran University



Gumilar Utamas Nugraha Alumni Faculty of Geology, Padjadjaran University. He received the B. Sc. Degree of Physics from Indonesia University of Education, Indonesia, master degree of Geological Engineering from Padjadjaran University, Indonesia. interest as well on the Hidrogeophysics, GIS &Remote

Sensing, Earth modeling using MATLAB, FORTRAN, JAVA & C++



Pulung Arya Pranantya he is a Researcher at Research Center for Water Resources, Research and Development Agency, Ministry of Public Works and Housing, Indonesia. He received the B. Sc. Degree from Trisakti University, master degree from Bandung Institute of Technology, Indonesia and Doctor degree

from Padjadjaran University.

Volume 6 Issue 9, September 2017 www.ijsr.net Licensed Under Creative Commons Attribution CC BY