Comparative Study on Concrete Box Girder (Single & Double Cells) Bridges Using Finite Element Method

Pampana Geetha Ramesh¹ Dr. P. V. Surya Prakash²

¹PG Scholar, PYDAH College of Engineering, Kakinada, India

²Phd, Professor PYDAH College of Engineering Kakinada, India

Abstract: Bridge construction today has achieved a worldwide level of importance. Bridges are the key elements in any road network and use of reinforced girder type bridges gaining popularity in bridge engineering fraternity because of its better stability, serviceability, economy, aesthetic appearance and structural efficiency. Generally for long span Box girder bridges are more structural efficient. Box girder resists the torsional rigidity and suited for significant curvature. For this study, Four different bridge girders are considered namely Rectangular Single and Double cell Box Girder (RSBG & RDBG), Trapezoidal Single and Double cell Box Girder (TSBG & TDBG) of spans 20 m, 30 m, 40m and 50m. Linear Static and Modal Analysis are performed on all the considered bridge girders using SAP2000 bridge wizard. IRC Class AA Tracked Loading system is considered for the analysis. A comparative report on dynamic Characteristics of all the considered bridge girders using SAP2000.

Keywords: Stiffness, modal analysis, Linear Static analysis, Loading system, Dynamic Characteristics

1. Introduction

1.1 General

Bridges are defined as structures which are provided a passage over a gap without closing way beneath. They may be needed for a passage of railway, roadway, footpath and even for carriage of fluid, bridge site should be so chosen that it gives maximum commercial and social benefits, efficiency, effectiveness and equality. Bridges are nation's lifelines and backbones in the event of war. Bridges symbolize ideals and aspirations of humanity. They span barriers that divide, bring people, communities and nations into closer proximity. Bridge construction constitutes an importance element in communication and is an important factor in progress of civilization, bridges stand as tributes to the work of civil engineers.

1.2 Box Girder Bridge Deck

A box girder bridge is a bridge in which the main beams comprise girders in the shape of a hollow box. The box girder normally comprises either prestressed concrete, structural steel, or a composite of steel and reinforced concrete. It is typically rectangular or trapezoidal in cross section. Box girder bridges are commonly used for highway flyovers and for modern elevated structures of light rail transport. The box girder can also be part of portal frame bridges, arch bridges, cable-stayed and suspension bridges of all kinds. Box girder decks are cast-in-place units that can be constructed to follow any desired alignment in plan, so that straight, skew and curved bridges of various shapes are common in the highway system. Because of high torsional resistance, a box girder structure is particularly suited to bridges with significant curvature.



Figure 1.1: Box Girder Bridge

SAP2000 can perform both linear static and multi-step static analysis. Certain types of load patterns are multi-stepped, meaning that they actually represent many separate spatial loading patterns applied in sequence. These include the vehicle, live, and wave types of load patterns. SAP2000 dynamic analysis capabilities include the calculation of vibration modes using Ritz or Eigen vectors, responsespectrum analysis, and time-history analysis for both linear and nonlinear behavior.

2. Geometrical Configuration of the Bridge Decks

2.1.1 Rectangular Single cell Box Girder

Table 2.1:	Geometrical paramet	ers of the	Rectangular
	Single cell Box Girde	er (RSBC	ή)

Geometrical Parameter	Dimensions (m)
Span of the Bridge Deck	20
Total Width of the Deck	8.7
Carriage way Width of the Deck	7.5
Overall Depth of deck	1.2
Width of the Beam	0.3
Thickness of the Deck slab	0.25
Cross girder width	0.3
No. of cross girders	5



Figure 2.1: Cross section of Rectangular Single cell Box Girder.

Considered different span of the girder is 20m, 30m, 40m and 50m with a total depth of 1.2m, 1.8m, 2.4m and 3.0m respectively.

2.1.2 Rectangular Double cell Box Girder

 Table 2.2: Geometrical parameters of the Rectangular

 Double cell Box Girder(RDBG)

Double cell Dox Glidel(RDDG)			
Geometrical Parameter	Dimension		
Span of the Bridge Deck	20m		
Total Width of the Deck	8.7 m		
Width of the Deck	7.5 m		
Depth of deck	1.2m		
Width of the beam	0.3m		
Thickness of the Deck slab	0.25m		
Thickness of the soffit slab	0.25m		
Cross girder	0.3m		
No. of cross girders	5		



Figure 2.2: Cross section of Rectangular Double cell Box Girder

Considered different span of the girder is 20m, 30m, 40m and 50m with a total depth of 1.2m, 1.8m, 2.4m and 3.0m respectively.

2.1.3 Trapezoidal Single cell Box Girder

 Table 2.3: Geometrical parameters of the Trapezoidal

 Single Cell Box Girder (TSBG)

0	
Geometrical Parameter	Dimension
Span of the Bridge Deck	20m
Total Width of the Deck	8.7 m
Width of the Deck	7.5 m
Depth of deck	1.2m
Width of the beam	0.3m
Thickness of the Deck slab	0.25m
Thickness of the soffit slab	0.25m
Cross girder	0.3m
No. of cross girders	5



Figure 2.3: Cross section of Trapezoidal Single cell Box Girder Considered different span of the girder is 20m, 30m, 40m and 50m with a total depth of 1.2m, 1.8m, 2.4m and 3.0m respectively.

2.1.4 Trapezoidal Double cell Box Girder

 Table 2.4: Geometrical parameters of the Trapezoidal

 Double cell Box Girder (TDBG)

Double tell Dox Glider (IDDG)		
Geometrical Parameter	Dimension	
Span of the Bridge Deck	20m	
Total Width of the Deck	8.7 m	
Width of the Deck	7.5 m	
Depth of deck	1.2m	
Width of the beam	0.3m	
Thickness of the Deck slab	0.25m	
Thickness of the soffit slab	0.25m	
Cross girder	0.3m	
No. of cross girders	5	



Figure 2.4: Cross section of Trapezoidal Double cell Box Girder

Considered different span of the girder is 20m, 30m, 40m and 50m with a total depth of 1.2m, 1.8m, 2.4m and 3.0m respectively.

2.2 Material Properties of the Bridge Girders

Table 3.5, shows the material properties of the bridge girders.

an of the buildes sinds

Table 2.5: Properties of the bridge girders			
Concrete	Density	25 kN/m ³	
	Poisson's Ratio	0.2	
	Young's Modulus	33.5E+06 kN/m ²	

	Poisson's Katio	0.2
	Young's Modulus	33.5E+06 kN/m ²
	Grade Of Concrete	M25
Steel	Density	78.5 kN/m ³
	Poisson's Ratio	0.3
	Young's Modulus	200E+06 kN/m ²
	Yield Stress, F _v	0.6 GPa

2.3 Loads Considered for the Study

Dead load and moving loads are considered based on IRC: 6-2010.

According to IRC: 6-2010, and other parameters we considered

Dead Load (IRC 875 Part I)

Moving Load (IRC 6 - 2010)

IRC Class AA Tracked Vehicle is considered for this study.

3. Results

3.1 Natural Time Period and Frequencies

Modal analysis is performed on different types of girders namely T-Bridge girder, Box Girder single cell, Box girder multi cell, box girder slope single cell and box girder slope

Volume 7 Issue 6, June 2018

www.ijsr.net

multi cell and the resulting mode shapes are noted down for different spans. In the present analysis, only 3 modes are considered.Table 4. shows the values of time period and frequencies for different girders and for different spans. As time period is inversely proportional to frequency, the Bridge with higher frequency values showed lower time period values

 Table 3.1: Natural Time Period and Frequencies for

 Different girders for 20m Span

GIRDERS	Time Period (sec)	Frequency (cyc/sec)	
RSBG	0.18	5.32	
RDBG	0.17	5.73	
TSBG	0.19	5.29	
TDBG	0.17	5.69	

3.2 Mode Shapes

Modal analysis is performed on different spans and different types of bridge girders and mode shapes are shown below.

3.3 For 20m Span

3.3.1 (a) Rectangular Single cell Box Girder



Figure 3.1: First Mode Shape for Rectangular Single cell Box Girder 20m Span.

3.3.1 (b) Rectangular Double cell Box Girder



Figure 3.2: First Mode Shape for Rectangular Double cell Box Girder 20m Span.

3.3.1 (c) Trapezoidal Single cell Box Girder



Figure 3.3: First Mode Shape for Trapezoidal Single cell Box Girder 20m Span

3.3.1 (d) Trapezoidal Double cell Box Girder



Figure 3.4: FirstMode Shape for Trapezoidal Double cell Box Girder 20m Span.



Figure 3.5 Frequency (cyc/sec) Values For different girders shapes for 20m Span

From figure 3.5, it is observed that the maximum frequency is for Rectangular Double cell Box Girder (RDBG) in all considered girders. It is observed that there is an increase in stiffness of 2%, 1% for RDBG and TDBG and decrease of 0.07% for TSBG when compared to RSBG.

Table 3.2: Natural Time Period and Frequencies for	•
Different girders for 30m Span	

	0	1
GIRDERS	Time Period (sec)	Frequency (cyc/sec)
RSBG	0.23	4.23
RDBG	0.22	4.51
TSBG	0.22	4.15
TDBG	0.21	4.61

3.3.2 For 30m Span

3.3.2 (a) Rectangular Single cell Box Girder



Figure 3.6: First Mode Shape for Rectangular Single cell Box Girder 30m Span.

Volume 7 Issue 6, June 2018 <u>www.ijsr.net</u>

3.3.2 (b) Rectangular Double cell Box Girder



Figure 3.7 First Mode Shape for Rectangular Double cell Box Girder 30m Span.

3.3.2 (e) Trapezoidal Single cell Box Girder



Figure 3.8 First Mode Shape for Trapezoidal Single cell Box Girder 30m Span.

3.3.2 (d) Trapezoidal Double cell Box Girder



Figure 3.9 First Mode Shape for Trapezoidal Double cell Box Girder 30m Span



Figure 3.10 Frequency (cyc/sec) Values For different girders shapes for 30m Span

From figure 3.10, it is observed that the maximum frequency is for Rectangular Double cell Box Girder (RDBG) in all considered girders. It is observed that there is an increase in stiffness of 6.6%, % for RDBG and TDBG and decrease of 8.9% for TSBG when compared to RSBG.

Table 3.3: Natural Time Period and Frequencies forDifferent girders for 40m Span

	Ų	1
GIRDERS	Time Period (sec)	Frequency (cyc/sec)
RSBG	0.35	2.84
RDBG	0.34	2.86
TSBG	0.35	2.82
TDBG	0.35	2.83

3.3.3 For 40m Span

3.3.3 (a) Rectangular Single cell Box Girder



Figure 3.11 First Mode Shape for Rectangular Single cell Box Girder 40m Span.

3.3.3 (b) Rectangular Single cell Box Girder



Figure 3.12 First Mode Shape for Rectangular Single cell Box Girder 40m Span

3.3.3 (c) Trapezoidal Single cell Box Girder



Figure 3.13 First Mode Shape for Trapezoidal Single cell Box Girder 40m Span.

3.3.3 (d) Trapezoidal Double cell Box Girder



Figure 3.14: First Mode Shape for Trapezoidal Double cell Box Girder 40m Span



Figure 3.15: Frequency (cyc/sec) Values For different girders shapes for 40m Span

From figure 3.15, it is observed that the maximum frequency is for Rectangular Double cell Box Girder (RDBG) in all considered girders. It is observed that there is an increase in stiffness of 2%, 1% for RDBG and TDBG and decrease of 0.07% for TSBG when compared to RSBG.

Volume 7 Issue 6, June 2018 <u>www.ijsr.net</u>

Table 3.4: Natural	Time Period	and Frequ	uencies for
Differer	nt girders for f	50m Span	

Different griders for 50m 5pan				
GIRDERS	Time Period (sec)	Frequency (cyc/sec)		
RSBG	0.18	5.32		
RDBG	0.17	5.73		
TSBG	0.19	5.29		
TDBG	0.17	5.69		

3.3.4 For 50m Span

3.3.4 (a) Rectangular Single cell Box Girder



Figure 3.16 First Mode Shape for Rectangular Single cell Box Girder 50m Span.

3.3.4 (b) Rectangular Double cell Box Girder



Figure 3.17: First Mode Shape for Rectangular Double cell Box Girder 40m Span.

3.3.4 (c) Trapezoidal Single cell Box Girder



Figure 3.18: First Mode Shape for Trapezoidal Single cell Box Girder 50m Span.

3.3.4 (d)Trapezoidal Double cell Box Girder



Figure 3.19: First Mode Shape for Trapezoidal Double cell Box Girder 50m Span.



Figure 3.20: Frequency (cyc/sec) Values For different girders shapes for 50m Span

From figure 3.20, it is observed that the maximum frequency is for Rectangular Double cell Box Girder (RDBG) in all considered girders. It is observed that there is an increase in stiffness of 7.7%, 6.9% for RDBG and TDBG and decrease of 0.5% for TSBG when compared to RSBG.

3.3 Stiffness for Different Girders

Below results shows the stiffness values obtained for different types of girders with 4 different spans subjected to Class AA Tracked Vehicle.

$$f_{
m n}=rac{1}{2\pi}\sqrt{rac{k}{m}}$$

f=natural frequency (cycles/sec) m=mass (kg) k=stiffness (N/m)

Table 3.6: Frequencies (cyc/sec) and Stiffness(kN/m) forDifferent girders for 20m Span

GIRDERS	Frequency (cyc/sec)	Stiffness (kN/m)
RSBG	5.32	122.20
RDBG	5.73	144.74
TSBG	5.29	116.20
TDBG	5.69	137.49

 Table 3.7: Frequencies (cyc/sec) and Stiffness(kN/m) for

 Different girders for 30m Span

GIRDERS	Frequency (cyc/sec)	Stiffness (kN/m)
RSBG	4.23	80.03
RDBG	4.51	94.18
TSBG	4.35	81.49
TDBG	4.61	95.07

Table 3.8. Frequencies (cyc/sec) and Stiffness(kN/m) forDifferent girders for 40m Span

	0	
GIRDERS	Frequency (cyc/sec)	Stiffness (kN/m)
RSBG	2.84	37.46
RDBG	2.86	39.81
TSBG	2.82	35.70
TDBG	2.83	37.81

 Table 3.9: Frequencies (cyc/sec) and Stiffness (kN/m) for

 Different girders for 50m Span

	0	
GIRDERS	Frequency (cyc/sec)	Stiffness (kN/m)
RSBG	2.26	24.72
RDBG	2.23	25.58
TSBG	2.25	23.77
TDBG	2.2	24.21

Volume 7 Issue 6, June 2018

<u>www.ijsr.net</u>

3.5 Comparison of Stiffness with different Girders



Figure 3.21: Stiffness (kN/m) Values for different girders shapes for 20m Span.

From figure 3.21, it is observed that the maximum stiffness is for Rectangular Double cell Box Girder (RDBG) in all considered girders. It is observed that there is an increase in stiffness of 18.4%, 12.5% for RDBG and TDBG and decrease of 4.9% for TSBG when compared to RSBG.



Figure 3.22: Stiffness(kN/m) Values For different girders shapes for 30m Span.

From figure 3.22, it is observed that the maximum stiffness is for Rectangular Double cell Box Girder (RDBG) in all considered girders. It is observed that there is an increase in stiffness of 17.6%, 18.7% for RDBG and TDBG and decrease of 18.7% for TSBG when compared to RSBG.



Figure 3.23: Stiffness (kN/m) Values for different girders shapes for 40m Span

From figure 3.23, it is observed that the maximum stiffness is for Rectangular Double cell Box Girder (RDBG) in all considered girders. It is observed that there is an increase in stiffness of 6.2%, 0.9% for RDBG and TDBG and decrease of 4.6% for TSBG when compared to RSBG.



Figure 3.24: Stiffness (kN/m) Values for different girders shapes for 50m Span

From figure 3.24, it is observed that the maximum stiffness is for Rectangular Double cell Box Girder (RDBG) in all considered girders. It is observed that there is an increase in stiffness of 3.4%, 3.3% for RDBG and TDBG and decrease of 3.8% for TSBG when compared to RSBG

4. Conclusions

For all considered spans Rectangular Double cell Box Girder (RDBG) having maximum stiffness when compared to all other considered girders.

For all considered spans due to dead and moving load Rectangular Double cell Box Girder (RDBG) having minimum deflection when compared to all other considered girders.

References

- [1] Abhishek Panda "Analysis and Design of T- Beam Bridge Super Structure Using Limit State Method" International Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395-0056 Volume: 02 Issue: 07 July-2014.
- [2] Abrar Ahmed, R.B. Lokhande "Comparitive Analysis and Design of T- Beam and Box Girders." International Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395-0056 Volume: 04 Issue: 07 July-2017.
- [3] Anil kumar H, B S Suresh Chandra "Flexural Behavior of Longitudinal Girders of RC T-Beam Deck Slab Bridge". International Journal for Scientific Research & Development Vol. 3, Issue 05, 2015 ISSN (online): 2321-0613.
- [4] Anushia K Ajay, Asha U Rao, N.A. PremanandShenoy "Parametric Study of T beam Bridge" International Journal of Civil Engineering and Technology (IJCIET) Volume 8, Issue 6, June 2017.
- [5] Hafsa Farooq, Abdul Arafat Khan "Effect of restrainers on RC Bridge using Linear and Non-linear analysis" IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE) e-ISSN: 2278-1684,p-ISSN: 2320-334X, Volume 13, Issue 6.
- [6] Hemalatha A, Ashwin K.N, Dattatreya J.K, S.V.Dinesh "Analysis of RC Bridge Decks for selected National and International Standard Loadings using Finite Element Method". International Journal of Research in Engineering and Technology eISSN: 2319-1163 pISSN: 2321-7308.

Volume 7 Issue 6, June 2018

<u>www.ijsr.net</u>

- [7] Kanchan Sen Gupta and SomnathKarmakar "Investigations on Simply supported concrete bridge deck slab for IRC vehicle loadings using finite element analysis" Journal of Earth Sciences and Engineering, Volume 04, No 06 SPL, October 2011, PP. 716-719.
- [8] Mahantesh.S.Kamatagi, M. Manjunath "Comparative Study of design of longitudinal girder of T- Beam Bridge Using IRC 21-2000 & IRC 112-2011". International Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395-0056 Volume: 02 Issue: 06 Sep-2015.
- [9] Mulesh K. Pathak "Performance of RCC Box type Superstructure in Curved bridges" International Journal of Scientific & Engineering Research, Volume 5, Issue 1, January-2014 2257 ISSN 2229-5518.
- [10] M.G. Kalyanshetti and R.P. Shriram "Study on Effectiveness of Courbon's Theory in the Analysis of Tbeam Bridges". International Journal of Science and Engineering Research. Volume 4, Issue 3, March 2013.
- [11] P.J Barr., Yanadori, N., Halling, M.W., and Womack ,K.C. "Live-Load Analysis of a Curved I-Girder Bridge" ASCE Journal of Bridge Engineering. V. 12, No. 4, July/August 2007.
- [12] R. ShreedharSpurtiMamadapur "Analysis of T-beam Bridges using Finite Element Method". International Journal of Engineering and Innovative Technology (IJEIT). Volume 2, Issue 3, September 2012.PP 340-346.
- [13] Takashi Chou "Optimum Reinforced Concrete T-Beam Sections" by, Engrg., Shinshu Univ., Nagano, Japan, Journal of the Structural Division, 1977, Vol. 103, Issue 8, Pg. 1605-1617.

Author Profile

Pampana Geetha Ramesh is PG Scholar, PYDAH College of Engineering, Kakinada, India

Dr.P.V.Surya Prakash, Phd, Professor Department of Civil Engineering PYDAH College of Engineering, Kakinada,India