

# Optimization of Shear Wall Locations in Irregular G+20 Story Building

Vineet Kumar Singh

M.TECH Student (Structural Engineering), Department of Civil Engineering, Maharishi University of Information Technology, Lucknow

**Abstract:** Today, tall structures have turned out to be overall engineering wonder. From past earthquakes, it is demonstrated that a significant number of structure are absolutely/somewhat harmed because of earthquake and now-adays it has turned out to be important to decide seismic reactions over such structures. Structural analysis is a branch which includes in the assurance of structures with a specific end goal to foresee the reactions of genuine structures, for example, structures, spans, trusses and so on. Basic outlining requires basic investigation and seismic examination of any structure before development. All together satisfy the prerequisite of this expanded populace in the constrained territory; the stature of building has turned out to be medium to tall structure. In this way, to guarantee wellbeing against seismic powers of multi-storied working, there is need of seismic examination study and planning quake protection structures. Amid earthquake, disappointment of structure begins from the purposes of a shortcoming. By and large, shortcoming happens because of geometry, mass brokenness and solidness of structure. That is the reason; structures fizzle amid earthquakes generally, because of vertical abnormality. The principle target this thesis is to think about the seismic investigation of structure for static and dynamic examination in standard minute opposing casing. We have thought about the private building, a G+9 storied structure for the seismic investigation and it is situated in Zone III LUCKNOW in India. Total structure was analysed by computer with using Etab 17.0.1 software.

**Keywords:** Seismic Analysis, G+20 , Bare RCC Frame , Tall Structure etc

## 1. Introduction

Earthquake has turned into a danger to human progress from the day of its reality, wrecking human lives, property and the man-made structures. Mass of a building being intended to controls seismic outline, notwithstanding building firmness, as earthquake initiates latency compel that winds up corresponding to the building's mass. Outlining structures ought to act flexibly amid the seismic shaking without harm may render the undertaking monetarily unreasonable? This paper is presented to improve the efficiency of real time earthquake risk mitigation methods and its capability of protecting structures, infrastructures and people, to investigate a multistorey RCC building (G +9 Story) for Zone 3, to look at seismic conduct of multistorey RCC building for specific shaking power regarding reactions, to contemplate the impacts of execution of multi-story working as far as seismic, to know the connection between various techniques for seismic investigation and their seismic reactions, to accomplish functional learning on basic investigation, seismic examination, outlining and specifying of auxiliary segments utilizing standards of Earthquake Resistant Analysis.

### 1.1. Moment Resisting Frames

The structure whose members and joints resist the forces principally caused by flexure is Moment Resisting Structure

#### 1.1.1. Ordinary Moment Resisting Frame (OMRF):

The moment resisting frame which are designed withno uncommon consideration towards malleable nature of the frame are called ordinary moment resisting frames.

#### 1.1.2. Special Moment Resisting Frame (SMRF)

The moment resisting structure which are intended to have malleable nature are called as special moment resisting

frames. The design is done according to the requirements specified in IS-13920. The earthquake resistant designs of structures are considering the accompanying magnitudes of an earthquake.

### 1.2. Design Basis Earthquake (DBE)

The earthquake whose likelihood of event is no less than one during the structure design life is called design basis earthquake.

### 1.3 Maximum Considered Earthquake (MCE)

The earthquake whose expected intensity is most extreme that can occur in a specific zone or region is called maximum considered earthquake. The maximum values are considered according to code. The design approach recommended by IS: 1893-2016 is depends on the accompanying standards.

- 1) The structure ought to have the quality to withstand minor earthquakes less than DBE without any damage.
- 2) The structure should have the capacity to oppose quakes equivalent to DBE without significant structural damage though some non-structural damage may occur.
- 3) The structure should withstand an earthquake equivalent to MCE without fall.

### 1.4 Literature Survey

Sayed O.et al. (2017) [1], concentrated his examination on the impact of infill and mass inconsistency on various floor in RC structures. The outcomes were presumed that the block infill upgrades the seismic execution of the RC structures what's more, poor seismic reactions were appeared by the mass sporadic building, thusly it ought to be maintained a strategic distance from in the seismic defenceless districts. Khan et al.(2016) [2], featured the impact of mass inconsistency on various floor in RCC

Volume 8 Issue 7, July 2019

[www.ijsr.net](http://www.ijsr.net)

Licensed Under Creative Commons Attribution CC BY

structures with as Reaction Spectrum investigation utilizing STAAD-Pro V8i programming. In the undertaking work seismic investigation of RCC structures with mass abnormality at various floor levels were done. Models are contrasted and each other for reaction regarding float and redirection. Reddy A. et al. (2015) [3], directed diagnostic examination for customary and sporadic structures to break down reaction of structures in seismic zone V.15 story building is considered and ETABS programming is utilized to show also, recreate building reaction. Examination is performed for static and dynamic techniques for investigation. Paper finished up conduct of unpredictable structures when contrasted with general structure. Mukundan H. et al. (2015) [4], discovered shear divider arrangement in building has been successful and efficient. A 10 story working in Zone IV is tried to diminish the impact of seismic tremor utilizing fortified solid shear dividers in the building. The outcomes are introduced subsequent to breaking down model utilizing ETABS programming and RSA strategy is utilized. Scientists additionally examined outcomes fluctuating thickness of shear dividers. It is presumed that shear dividers are more impervious to parallel loads in customary/Irregular structure and for more secure plan, the thickness of the shear divider ought to go between 150mm to 400mm. Mayuri D. Bhagwat et al.(2014) [5], G+12 multi-storeyed RCC building considering Koyna and Bhuj tremor is completed by utilizing time history examination and reaction range investigation. Seismic reactions of such building are nearly considered and displayed with the assistance of ETABS programming. Two time accounts (i.e. Koyna and Bhuj) have been utilized to create distinctive satisfactory criteria (base shear, story uprooting, story floats)

**2. Methodology**


If the structure not properly designed and constructed with required quality they may cause large destruction of structures due to earthquakes. Response spectrum analysis is a helpful procedure for seismic examination of structure when the structure indicates linear response. Extensive literature survey by referring books, specialized papers did to comprehend essential idea of subject.

- Selection of an appropriate plan of G+9, story building.
- Computation of loads and selection of preliminary cross-sections of different structural members.
- Geometrical modelling/demonstration and structural analysis of building for various loading conditions as per
- IS Codal provisions. Interpretation of results incorporate base shear, story float and story diversion.
- In the present work it is proposed to complete seismic investigation of multi-story RCC structures utilizing
- Response Spectrum Analysis method considering mass irregularity with the help of ETab 17.0.1 software.

**3. Analysis and Design of Building**


S No.	Description Of Structure	Values
1.	Material	Concrete (M30) and Reinforcement (Fe500)
2.	No. of Storeys	G+20(20 storey's)
3.	Plan	25.0mX25.0m
4.	Size of Beam	300 x 400 mm

5.	Size of Column	400 x 400 mm
6.	Floor Height	3.0 m
7.	Slab Thickness	150 mm
8.	Seismic zone	Zone 3
9.	Dead Load	5.5 kN/m
10.	Live Load	3 kN/m <sup>2</sup>



**4. Result**

Story	Story Drift (mm)	IS Code 1893:2016 Allowed Value (mm)
10	1.355	12
9	2.208	12
8	2.925	12
7	3.474	12
6	3.872	12
5	4.141	12
4	4.311	12
3	4.462	12
2	5.113	12
1	9.829	12



**5. Conclusion**

According to **IS 1893-2016**, allowable drift is calculated as **h/250**, Where, h is story height of building above the ground level in millimeters (mm).

Adopting the above practice the maximum drift in X and Y direction must lie within 12 mm (3000/250 = 12) where 3000 mm is the height of the story building. As the above research work the Max. story drift is shown 9.829 mm at

story 1 which is under the permissible limit of IS 1893:2016 code (i.e. 12 mm allowed value).

## References

- [1] O.Esmaili, 2008. "Study of structural RC Shear Wall System in a 56-storey RC tall Building".
- [2] Anila Anna Samson, 2014. "Performance of Shear Wall Building during Seismic Excitations".
- [3] Le Yee Mon, 2014. "Comprative Study on Dynamic Analysis of Irregular Building with Shear Wall".
- [4] Ravikanth Chittiprolu, 2014. "Significance of shear wall in high rise irregular buildings".
- [5] Dr.Haider S. AL-Jubair, 2014. "The effect of Shear Walls on Seismically Isolated Building Of Variable Geometric configurations".
- [6] Mohammad Aminnia, 2015. "The Effects of Placement and Cross-Section Shape of Shear Walls in Multi-Story RC Buildings with Plan Irregularity on Their Seismic Behaviour by Using Nonlinear Time History Analyses".
- [7] Shrath Irappa kammar, 2015. "Non-linear Static Analysis of Asymmetric building".
- [8] Dr.C.P.Pise, 2016. "EFFECT OF POSITIONING OF RC SHEAR WALLS OF DIFFERENT SHAPES ON SEISMIC PERFORMANCE OF BUILDING RESTING ON SLOPING GROUND".
- [9] Akash S.Waghmode, 2016. "Compresion of Plan Irregularity of MULTISTORIED SHEAR WALL Structure for wind Analysis".

