

References

- [1] B H Robert, "Plasma sprayed coatings; principles and applications". NY: VCH Publ; 132, (1996).
- [2] D Maejka, B Benko, "Plasma spraying of metallic and ceramic materials", NY: John Wiley; 156, (1989).
- [3] T Liu, C L White, IN: Koch CC, Liu CT, Stollof NS, editors. High temp ordered intermetallic alloys. Mat Res Soc, 39.P.365.
- [4] W Cahn, "Load-bearing ordered intermetallic compounds—a historical view" MRS Bull; 5:18. (1991)
- [5] J Z Chen, H Herman, S Safai, "Evaluation of NiAl and NiAl-B deposited by vacuum plasma spray", *J Therm Spray Technol*;2:357, (1993)
- [6] C T Liu, V K Sikka, "Nickel aluminides for structural uses", *J Metals*; **38**:13, (1986)
- [7] M Ivošević, R Knight, S R Kalidindi, G R Palmese, J K Sutter, 'Adhesive/cohesive properties of thermally sprayed functionally graded coatings for polymer matrix composites", *J Therm Spray Tech*; **14**(1):45, (2005)
- [8] D Niebuhr, M Scholl, "Synthesis and performance of plasma-sprayed polymer/ steel coating system", *J Therm Spray Tech*; **14**(4): 487, (2005)
- [9] T. A Stolarski, "Tribology in Machine Design", HeimanNewnes, UK. (1990).
- [10] Päivi Kivikytö-Reponen, "Correlation of Material Characteristics and Wear of Powder Metallurgical Metal Matrix Composites", Doctoral Theses in Materials and Earth Sciences, Helsinki University of Technology, Laboratory of Materials Science, Espoo (2006).
- [11] M. Prasannakumar, K. Sadashivappa, G. P. Prabhukumar, and S. Basavarjappa, "Dry sliding wear behaviour of granet particles reinforced zinc-aluminium alloy metal matrix composites", *Materials science*; **12**(3): 209, (2006).
- [12] S. K. Acharya, V. Dikshit, And P. Mishra, "Erosive Wear Behaviour of Redmud Filled Metal Matrix Composite", *Journal of Reinforced Plastics and Composites*; **27**(2): 145, (2008).
- [13] S. C. Mishra, S. Das, A. Satapathy, P. V. Ananthapadmanabhan and K.P. Sreekumar, "Erosion Wear Analysis of Plasma Sprayed Ceramic Coating Using the Taguchi Technique", *Tribology Transactions*; **52**: 401-4, (2009).
- [14] S. P. Sahu, , A Satapathy, D Mishra, A Patnaik and K. P Sreekumar, "Tribo-Performance Analysis of Fly Ash–Aluminum Coatings Using Experimental Design and ANN", *Tribology Transactions*; **53**: 533-42, (2010).
- [15] S .P .Sahu, A. Satapathy, A Patnaik, K. P. Sreekumar and P. V Ananthapadmanabhan, "Development, characterization and erosion wear response of plasma sprayed fly ash–aluminum coatings", *Materials and Design*; **31**: 1165–73, (2010).
- [16] H Thomas, Kosel. ASM hand book: Friction, lubrication, and wear technology. ASM Inter Hand book Comm; **18**: 371–2, (1992).
- [17] Y Sahin. "The prediction of wear resistance model for the metal matrix composites". *Wear*; **258**: 1717–22, (2005).

A W Ruff and L K Ives, "Measurement of s